



LOG CABIN FINISH GLOSS

NO. 15 CLEAR



PRODUCT INFORMATION

BEHR® LOG CABIN FINISH GLOSS is a quality product that contains a mildewcide that will assist in providing a surface film resistant to mildew. While this product does contain a mildewcide, it will not prevent mildew growth.

RECOMMENDED USES:

Use on exterior wood surfaces such as log and timber frame homes, siding, fencing and railings.

COMPLIES WITH THE BELOW AS OF 3/22/2011			
OTC	YES	CARB	YES
SCAQMD	YES	MPI #	197

PRODUCT SPECIFICATIONS:

Base:

- *No. 15 Clear, 128 oz.
- No. 16 Cedar, 128 oz.

Gloss: 80-100 @ 60°

Vehicle Type: Alkyd Dispersion

*Weight Per Gallon: 8.5 +/- 0.2 lbs./gal

*% Solids:

- By Volume: 29.4 +/- 2%
- By Weight: 30.7 +/- 2%

VOC: <275 (g/l)

Flash Point: Not Applicable

Zahn#2: 22-35 sec

Recommended Film Thickness:

- Wet: 8.0 Dry: 2.4 mils @ 200 SFPG
- Wet: 4.0 Dry: 1.2 mils @ 400 SFPG

Coverage: 200-400 Square Feet Per Gallon, depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

When working with more than one container of the same color, intermix to ensure color uniformity. DO NOT THIN PRODUCT. Stir product before and occasionally during application. Test product for penetration and color on a small hidden area before proceeding. Use a nylon/polyester bristle brush or pad applicator. Rolling should be limited to rough surfaces only. Use a 3/8" nap roller. Airless spray is recommended for experienced applicators only. Apply at a spread rate of 200-400 sq. ft. (18-37 m²) per gallon on the first coat and 300-400 sq. ft. (27-37 m²) per gallon on successive coats. Maintenance re-coating may be achieved by applying 2 coats at a spread rate of 200-400 sq. ft. (18-37 m²) per gallon over a clean, sound surface. 3-4 coats will provide maximum performance and added protection. Clean and recoat surface when finish no longer has gloss or luster or if the film is broken. Thoroughly seal the ends of the boards and all porous areas such as knots with several thin coats. Saturate surface leaving a wet sheen. Maintain a wet edge when applying. Back-brush during all application methods. Apply product end-to-end or to board lengths to prevent lap marks. Avoid applying product in direct sunlight or to hot surfaces.

APPLICATION TOOLS:

- Brush:** Nylon/polyester
- Roller:** Use 3/8"-1/2" nap cover on smooth surfaces and 1/2"-3/4" on rough, porous surfaces.
- Air-less Spray:** At packaged consistency
- Tip:** .015" - .021"
- Filter:** 60 mesh
- Thinning:** (If required) No more than 1/2 pint of water per gallon.
- †Dry Time:** @ 77° & 50% RH
 - †To Touch: 8-12 hours
 - †To Recoat: 24 hours
 - †Full Cure: 2 weeks

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on floors.
- For best results, apply at temperatures between 40°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Brushes and other equipment can be cleaned with warm, soapy water. For disposal of empty containers and unused product, contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





LOG CABIN FINISH GLOSS

NO. 15 CLEAR

SURFACE PREPARATION:

Mildew Stains: All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m²). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength.

New Wood: Follow up mildew stain removal with BEHR® Premium 2-in-1 Wood Prep No. 63 after application to remove mill glaze to condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions.

Wood: WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

New Wood: Remove mill glaze with sandpaper or use BEHR® Premium 2-in-1 Wood Prep No. 63 to open the pores of the wood and follow all label instructions. For severe stains caused by mold, mildew, algae and fungus, apply BEHR® Premium Mold & Mildew Stain Remover No. 62 and follow all label instructions. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking where necessary and allow to dry completely. Patched and filled surfaces should be sanded smooth and dusted clean prior to coating.

Weathered Wood: †To remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood decks, siding, fences, shakes and shingles, use BEHR® Premium Stain & Finish Stripper No. 64 and follow all label instructions. Use BEHR® Premium 2-in-1 Wood Prep No. 63 and follow all label instructions to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae and fungus. Be sure to follow all label instructions.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: AN OXIDIZING OIL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING.

USE WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air and use a properly fitted respirator (NIOSH approved for organic vapor with P Series particulate prefilter). Obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

IMPORTANT! STORAGE AND DISPOSAL: DANGER!

Rags, steel wool and waste soaked with this BEHR LOG HOME GLOSS FINISH may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.

