

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



**BEHR® INT/EXT
MASONRY, STUCCO
& BRICK FLAT
PAINT
NO. 270 WHITE**

RECOMMENDED USES:

Great for new or old, previously coated interior or exterior vertical surfaces such as brick, masonry, stucco, concrete, cement, slate, stone, cinder block, adobe and clay.

AVAILABLE IN: Gallon & Five Gallon

COLORS

No. 270 White

Custom colors plus computer color matching available.

TINT BASE / MAX TINT*

No. 270 – 126 oz.

White – 4 oz.

FINISH

Flat

*Sheen Level 0 - 3.5 @85°

*Substrate Dependant

COVERAGE RATE

Rough: 250-300 sq. ft. per gallon

Smooth: up to 400 sq. ft. per gallon

4 mils wet, 1.20 mils dry

DRYING TIME

@77°F & 50% humidity*

*Longer dry time required in cooler temperatures or in higher humidity.

To Touch: 2-3 Hours

Recoat: 4 Hours

Cured: Two Weeks

PRIMERS

No. 436 Exterior Water Based Primer

COMPOSITION

Vehicle/Active Ingredient:

Acrylic Latex

Percent Solids By Volume:

31%

Percent Solids By Weight:

46%

Weight Per Gallon:

10.8 lbs.

VOC

36gm/l Material (Includes Water)

100 gm/l Coating (Excludes Water)

Flashpoint

N/A

MSDS

Available @ www.behr.com

Or 1-800-854-0133 Ext. 2

Clean Up

Soap & Water. Recycle or dispose of paint call 1-800-CLEANUP (U.S.A. only) www.earth911.org

APPLICATION TOOLS

Airless Spray: Filter: 60 mesh Tip: .015-.017

Conventional Spray: See manufacturer recommendations

Brush: Nylon/Polyester blend

Roller: ¾" - 1" Nap. Depending on the surface texture.

Thinner: Do Not Thin. If spraying only, thin no more than ½ pint of water per gallon.

SURFACE PREPARATION

Remove all loose, peeling paint using a scraper or sandpaper. Wash off all chalk, dirt, grease, soap and oil-build-up with mild detergent; remove mildew with BEHR No. 62 Multi-Surface Deck-Prep™ Cleaner & Mildew Stain Remover or bleach and water. Rinse and allow to dry. Scuff sand glossy surfaces. Patch holes and cracks. Caulk joints and seams.

APPLICATION

Use product when surface and air temperature are between 50°- 90°F. Intermix multiple containers to ensure color and sheen uniformity. Certain colors may require multiple coats. Apply using a high quality roller cover, nylon/polyester brush or airless sprayer.

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

**To Consult with a Technical Service Representative call
1-800-854-0133 Ext. 2**

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



**BEHR® INT/EXT
MASONRY, STUCCO
& BRICK FLAT
PAINT
NO. 271
PASTEL BASE**

RECOMMENDED USES:

Great for new or old, previously coated interior or exterior vertical surfaces such as brick, masonry, stucco, concrete, cement, slate, stone, cinder block, adobe and clay.

AVAILABLE IN: Gallon & Five Gallon

COLORS

No. 271 Pastel Base

Custom colors plus computer color matching available.

TINT BASE / MAX TINT*

No. 271 – 120 oz.

Pastel Base – 8 oz.

FINISH

Flat

*Sheen Level 0 - 3.5 @85°

*Substrate Dependant

COVERAGE RATE

Rough: 250-300 sq. ft. per gallon

Smooth: up to 400 sq. ft. per gallon

4 mils wet, 1.30 mils dry

DRYING TIME

@77°F & 50% humidity*

*Longer dry time required in cooler temperatures or in higher humidity.

To Touch: 2-3 Hours

Recoat: 4 Hours

Cured: Two Weeks

PRIMERS

No. 436 Exterior Water Based

Primer

COMPOSITION

Vehicle/Active Ingredient:

Acrylic Latex

Percent Solids By Volume:

33%

Percent Solids By Weight:

47%

Weight Per Gallon:

10.6 lbs.

VOC

36gm/l Material (Includes Water)

100 gm/l Coating (Excludes Water)

Flashpoint

N/A

MSDS

Available @ www.behr.com

Or 1-800-854-0133 Ext. 2

Clean Up

Soap & Water. Recycle or dispose of paint call 1-800-CLEANUP (U.S.A. only) www.earth911.org

APPLICATION TOOLS

Airless Spray: Filter: 60 mesh Tip: .015-.017

Conventional Spray: See manufacturer recommendations

Brush: Nylon/Polyester blend

Roller: ¾" - 1" Nap. Depending on the surface texture.

Thinner: Do Not Thin. If spraying only, thin no more than ½ pint of water per gallon.

SURFACE PREPARATION

Remove all loose, peeling paint using a scraper or sandpaper. Wash off all chalk, dirt, grease, soap and oil-build-up with mild detergent; remove mildew with BEHR No. 62 Multi-Surface Deck-Prep™ Cleaner & Mildew Stain Remover or bleach and water. Rinse and allow to dry. Scuff sand glossy surfaces. Patch holes and cracks. Caulk joints and seams.

APPLICATION

Use product when surface and air temperature are between 50°- 90°F. Intermix multiple containers to ensure color and sheen uniformity. Certain colors may require multiple coats. Apply using a high quality roller cover, nylon/polyester brush or airless sprayer.

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

**To Consult with a Technical Service Representative call
1-800-854-0133 Ext. 2**