



EXTERIOR SEMI-TRANSPARENT COLOR
DECK, FENCE & SIDING WOOD STAIN

NO. 3077 & 3088 TINT BASES



PRODUCT INFORMATION

BEHR® Semi-Transparent Deck, Fence & Siding Wood Stain is a wood grain enhancing stain that provides a UV protecting & water repellent for all types of woods.

RECOMMENDED USES:

Exterior properly prepared wood and composite surfaces such as: plywood, fences, patio covers, shingles, shakes, siding, decks and railings.

COMPLIES WITH THE BELOW AS OF 3/22/2011			
OTC	YES	CARB	YES
SCAQMD	YES		

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. 3088 Tint Base 124 oz / 4 oz

No. 3077 Deep Base 120 oz / 8 oz

PRE-MIXED COLORS:

No. 3365 Cape Cod Gray

No. 3330 Redwood

No. 3533 Cedar Naturaltone

Vehicle Type: Alkyd/Acrylic

*Weight Per Gallon: 8.6 lbs at +/- 2%

*% Solids:

By Volume: 17% +/- 2%

By Weight: 21% +/- 2%

VOC: <100 (g/l)

Flash Point: Not Applicable

*Coverage: 2 coats are required for optimal appearance and durability. Spread rate of the first coat is approximately 250-300 sq. ft. per gallon (24-28 m² per 3.79 L). Apply a thinner second coat at a spread rate of approximately 500-600 sq. ft. per gallon (46-55 m² per 3.79 L).

APPLICATION:

Brush: Nylon/polyester or Pad Applicator

Roller: Use 3/8"

Airless Spray: At packaged consistency

Tip: .015"

Filter: 60 mesh

†Dry Time: @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

†To Touch: 1-2 Hours

†Recoat: Apply 2nd coat within 24 Hours

†Full Cure: 72 Hours

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on floors
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





EXTERIOR SEMI-TRANSPARENT COLOR DECK, FENCE & SIDING WOOD STAIN NO. 3077 & 3088 TINT BASES

SURFACE PREPARATION:

Mildew Stains: All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m²). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength.

New Wood: Follow up mildew stain removal with BEHR® Premium 2-in-1 Wood Prep No. 63 after application to remove mill glaze to condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions.

Wood: Remove mill glaze with sandpaper or use BEHR® Premium 2-in-1 Wood Prep No. 63 to open the pores of the wood and follow all label instructions. For severe stains caused by mold, mildew, algae and fungus, apply BEHR® Premium Mold & Mildew Stain Remover No. 62 and follow all label instructions. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth.

Weathered Wood Surfaces: †To remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood decks, siding, fences, shakes and shingles, use BEHR® Premium Stain & Finish Stripper No. 64 and follow all label instructions. Use BEHR® Premium 2-in-1 Wood Prep No. 63 and follow all label instructions to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae and fungus. Be sure to follow all label instructions.

GENERAL INFORMATION:

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING IN VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.

