



PREMIUM DECK, FENCE & SIDING STAIN & FINISH STRIPPER

NO. 64

PRODUCT INFORMATION

A ready-to-use exterior stripper designed to rapidly remove oil, latex-based, and 100% acrylic finishes such as semi-transparent stains, solid color stains and clear sealers. It also removes loose wood fibers to help ensure a sound surface prior to staining or painting. Created especially for use on deck and siding surfaces, it removes previous coatings from wood, tile, concrete, masonry, stucco, stone and brick.

RECOMMENDED USES:

Exterior latex, oil-based and 100% acrylic coatings on Wood Decks, Siding, Fences, Shakes and Shingles. Removes loose wood fibers without sanding. Ideal for unsightly stains caused by oil or rusty water on uncoated Tile, Concrete, Masonry, Stucco, Stone, and Brick. Not for interior use or on aluminum surfaces. May harm bare metal or painted surfaces.

PRODUCT SPECIFICATIONS:

No. 64 128 oz

Active Type: Sodium Hydroxide

***Weight per Gallon:** 8.9 +/- 0.2 lbs./gal

***% Solids:** By Weight: 11.5 +/- 2%

VOC (C.O.V.): 3.4 wt %

Flash Point: Not Applicable

Viscosity: Not Applicable

SURFACE PREPARATION:

STIR OR SHAKE WELL BEFORE OPENING. DO NOT THIN PRODUCT. Be sure to have the following: source for tap water, garden hose with nozzle, plastic sprayer or disposable brush, stiff bristle broom or brush and BEHR® PREMIUM 2-IN-1 WOOD PREP NO. 63. Surface must be dry. Do not apply in direct sunlight or on hot surfaces. Use product when air and surface temperatures are between 50°-90°F (10°-32°C). Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Wear protective clothing, goggles, chemical-resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge. Test in a small area for effectiveness, rinse and let dry before continuing. Prevent all rinse solution from entering storm drains.

APPLICATION:

Apply BEHR® PREMIUM STAIN & FINISH STRIPPER NO. 64 liberally using a nylon/poly brush or roller. Natural bristle brushes or lambs wool applicators are not recommended. Due to the viscosity or thickness of this product, DO NOT APPLY WITH A PUMP SPRAYER. Do not allow product to dry on wood; keep surface wet by misting with water and re-apply BEHR® PREMIUM STAIN & FINISH STRIPPER NO. 64 if drying occurs. Finish will begin to lift from the surface. Repeat process as needed to keep the surface wet during the removal period. Most deteriorated finishes will start to lift after about 5-45 minutes. The coating should easily rinse off when ready. When the finish starts to lift, lightly scrub the surface using a stiff bristle broom or brush. Rinse thoroughly with water from garden hose using nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. If some of the old finish remains on the surface, repeat application procedure or spot sand as needed. Use at a rate of approximately 50-150 sq. ft. (4-14m²) per gallon, depending on porosity and condition of surface. Some woods may darken after stripping. Use BEHR PREMIUM 2-IN-1 WOOD PREP NO. 63 on all wood surfaces to remove stains caused by mold & mildew, rejuvenate natural wood color and neutralize the stripping action. Follow all label instructions. This provides stability for reapplication of a new finish or sealer.

CLEAN UP:

Biodegradable. Rinse all equipment with water before storage or reuse. Clean with soap & water. Properly dispose of all soiled rags and protect unused product from freezing. For disposal of unused paint products, please contact your household refuse collection service.

DRY TIME:

Before applying a coating, allow the wood to dry for a minimum of 24 hours in warm, dry weather or longer in cool temperatures and/or high humidity. Surfaces must be thoroughly dry before applying any type of new finish, except those finishes that can be applied to dampened wood.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use when air and surface temperatures are below 50°F and above 90°F.
- Avoid heavy traffic for 24 hours.
- **CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

Wood: WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





PREMIUM DECK, FENCE & SIDING STAIN & FINISH STRIPPER

NO. 64

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

DANGER! CORROSIVE. WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS SODIUM HYDROXIDE. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION.

USE ONLY WITH ADEQUATE VENTILATION. Only use this product outdoors. Avoid contact with skin. Wear protective clothing, acid resistant rubber gloves and eye goggles. If properly used, a respirator may offer additional protection.

FIRST AID: Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.