

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



**BEHR®
FLAT FINISH ROOF
PAINT
No. 65
WHITE REFLECTIVE**

RECOMMENDED USES:

New or old Unglazed Tile, Masonry Shingle, Anchored Gravel, Aluminum/Metal Materials, Composition Sheets, Asphalt Shingle, Concrete or Cement Block, Urethane Foam, Slate or Wood shaken Wood shake Roofs. It is not intended to waterproof or repair roof leak. This product is intended to brighten roofs and reflect heat.

AVAILABLE IN: Gallon & Five Gallon

COLORS

No. 65 White

Tintable Bases/Max Tint

No. 65 – 126 oz.
White – 4 oz

Custom colors plus computer color matching

FINISH

Flat.
*Sheen Level 0-4.0 @ 85°
*Substrate Dependant

COVERAGE RATE

250 (23m²) sq. ft. per gallon on rough surfaces. 350 (32m²)sq. ft. per gallon for second coat. 350 (32m²) sq. ft. per gallons on smooth surfaces. 450 (42m²) sq. ft. for second coat. 4 mils wet, 1.3 mils dry

DRYING TIME

@77°F & 50% humidity*
*Longer dry time may be needed in cooler temperatures or higher humidity.

To Touch: 2 Hours
Recoat: 4 Hours
Cured: Two Weeks

PRIMERS

No. 436 Exterior Water-Based Primer
No. 434 Oil-Based Primer

COMPOSITION

Vehicle/Active Ingredient:

100% Acrylic

Percent Solids By Volume:

35%

Percent Solids By Weight:

53%

Weight Per Gallon:

11.8 lbs.

VOC

<250 g/l

Flashpoint

N/A

MSDS

Available @ www.behr.com
Or 1-800-854-0133 Ext. 2

Clean Up

Soap & Water. Recycle or dispose of unused product call 1-800-CLEANUP (U.S.A. only) www.earth911.org

APPLICATION TOOLS

Airless Spray: Filter: 60 mesh Tip: .015-.017

Conventional Spray: See manufacturer recommendations

Brush: Nylon/Polyester blend

Roller: 1" Nap roller. Depending on the surface texture.

Thinner: Do Not Thin. If spraying only, thin no more ½ pint of water per gallon

SURFACE PREPARATION

Replace brittle or cracked shingles. Clean all roof surfaces. Previously coated surface should be wire brushed or scraped to remove all loose coating. Remove mildew with BEHR® No. 62 Multi-Surface Deck-Prep™ Cleaner and Mildew Stain Remover or bleach and water. On galvanized metal, use a diluted solution of BEHR® No. 991 Concrete Etcher & Rust Remover to prepare surface. If applying on wood shake, clean with BEHR® No. 63 Wood Cleaner Brightener Conditioner. Follow directions on products labels. Rinse. Allow to dry for 24 hours. Prime all metal, asphalt and wood surfaces.

APPLICATION

Use product when surface and air temperature are between 50°-90°F. Intermix multiple containers, to ensure color and sheen uniformity. Apply starting at the top of the roof working down. Always maintain a wet edge.

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



BEHR®
FLAT FINISH ROOF
PAINT
No. 66
DEEP BASE

RECOMMENDED USES:

New or old Unglazed Tile, Masonry Shingle, Anchored Gravel, Aluminum/Metal Materials, Composition Sheets, Asphalt Shingle, Concrete or Cement Block, Urethane Foam, Slate or Wood shaken Wood shake Roofs. It is not intended to waterproof or repair roof leak. This product is intended to brighten roofs and reflect heat.

AVAILABLE IN: Gallon & Five Gallon

COLORS

No. 66 Deep Base

Tintable Bases/Max Tint

No. 66 – 116 oz.

Deep Base – 14 oz

Custom colors plus computer color matching

FINISH

Flat.

*Sheen Level 0-4.0 @ 85°

*Substrate Dependant

COVERAGE RATE

250 (23m²) sq. ft. per gallon on rough surfaces. 350 (32m²)sq. ft. per gallon for second coat. 350 (32m²) sq. ft. per gallons on smooth surfaces. 450 (42m²) sq. ft. for second coat. 4 mils wet, 1.3 mils dry

DRYING TIME

@77°F & 50% humidity*

*Longer dry time may be needed in cooler temperatures or higher humidity.

To Touch: 2 Hours

Recoat: 4 Hours

Cured: Two Weeks

PRIMERS

No. 436 Exterior Water-Based Primer

No. 434 Oil-Based Primer

COMPOSITION

Vehicle/Active Ingredient:

100% Acrylic

Percent Solids By Volume:

31%

Percent Solids By Weight:

44%

Weight Per Gallon:

11.8 lbs.

VOC

17gm/l Material (Includes Water)

50 gm/l Coating (Excludes Water)

Flashpoint

N/A

MSDS

Available @ www.behr.com

Or 1-800-854-0133 Ext. 2

Clean Up

Soap & Water. Recycle or dispose of unused product call 1-800-CLEANUP (U.S.A. only) www.earth911.org

APPLICATION TOOLS

Airless Spray: Filter: 60 mesh Tip: .015-.017

Conventional Spray: See manufacturer recommendations

Brush: Nylon/Polyester blend

Roller: 1" Nap roller. Depending on the surface texture.

Thinner: Do Not Thin. If spraying only, thin no more ½ pint of water per gallon

SURFACE PREPARATION

Replace brittle or cracked shingles. Clean all roof surfaces. Previously coated surface should be wire brushed or scraped to remove all loose coating. Remove mildew with BEHR® No. 62 Multi-Surface Deck-Prep™ Cleaner and Mildew Stain Remover or bleach and water. On galvanized metal, use a diluted solution of BEHR® No. 991 Concrete Etcher & Rust Remover to prepare surface. If applying on wood shake, clean with BEHR® No. 63 Wood Cleaner Brightener Conditioner. Follow directions on products labels. Rinse. Allow to dry for 24 hours. Prime all metal, asphalt and wood surfaces.

APPLICATION

Use product when surface and air temperature are between 50°-90°F. Intermix multiple containers, to ensure color and sheen uniformity. Apply starting at the top of the roof working down. Always maintain a wet edge.

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2