



ELASTOMERIC MASONRY, STUCCO & BRICK PAINT

NO. 68 ULTRA PURE WHITE®



PRODUCT INFORMATION

BEHR® ELASTOMERIC MASONRY, STUCCO & BRICK PAINT is a flexible, high-build coating designed to expand and contract, bridging hairline cracks in exterior, vertical masonry surfaces. This waterproofing paint is extremely durable and is mildew and dirt resistant. It has superior elasticity and elongation properties, stretching up to 600%. It passes Federal Specification TT-C-555b sec. 3.3.3, withstanding 98-mph wind-driven rain. This 100% acrylic latex formula provides a breathable film, releasing moisture that builds in walls. This low-sheen paint has excellent color retention and is available in 63 custom tinted colors.

RECOMMENDED USES:

Use on properly prepared and primed, vertical surfaces including stucco, masonry, concrete, concrete block or brick as well as adjacent wood and metal surfaces.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

*No. 68 Ultra Pure White® 124 oz / 6 oz

Sheen: 3.5-5.5 @ 85°

Vehicle Type: Acrylic Latex

***Weight per Gallon:** 10.8 +/- 0.2 lbs./gal

***% Solids:**

By Volume: 48.0 +/- 2%

By Weight: 59.6 +/- 2%

VOC: <50 g/l

Flash Point: Not Applicable

Viscosity: 120-130 KU

Elongation: 600%

Wind Driven Rain:

98 mph ASTM TT-C-555B

Perm Rating: 9 US Perms

***Recommended Film Thickness:**

Wet: 21.3 mils / Dry: 10.2 mils @ 75 SFPG

Wet: 12.8 mils / Dry: 6.1 mils @ 125 SFPG

***Coverage:** 75-125 Square Feet Per Gallon depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: Use 1 1/4" nap cover.

Air-less Spray: At packaged consistency

Tip: .025"-.029"

Filter: 60 mesh

Thinning: (If required) No more than 1/2 pint of water per gallon.

† **Dry Time:** @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

† To Touch: 4-6 hours

† To Recoat: 24 hours

† Full Cure: 2 weeks

RECOMMENDED PRIMER/SYSTEMS:

Masonry:

• BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

Masonry with pH Levels up to 13.0:

- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436
- BEHR® Interior/Exterior Basement & Masonry Waterproof No. 875 or BEHR® Interior/Exterior Concrete & Masonry Waterproof No. 870

Wood:

- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436
- BEHR PREMIUM PLUS® Interior/Exterior Oil-Based Primer & Sealer No. 434 on properly prepared surfaces.

Galvanized Metal, Metal & Aluminum:

- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

NEW SURFACES:

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

PREVIOUSLY PAINTED SURFACES:

- Use a full coat or spot prime with BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436, or use BEHR PREMIUM PLUS® Interior/Exterior Oil-Based Primer & Sealer No. 434 on properly prepared surfaces.

| COMPLIES WITH THE BELOW AS OF 3/22/2011 | | | |
|---|-----|-------|-----|
| OTC | YES | CARB | YES |
| SCAQMD | YES | MPI # | 113 |

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on floors.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Allow two weeks for full cure before washing or cleaning.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Clean all tools and equipment with soap and water. To recycle or dispose of paint, contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN.**

PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.

Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





ELASTOMERIC MASONRY, STUCCO & BRICK PAINT

NO. 68 ULTRA PURE WHITE®

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust, and all other foreign substances.

Mildew Stains: Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m²). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength. **New Wood:** Follow up mildew stain removal with BEHR® Premium 2-in-1 Wood Prep No. 63 after application to remove mill glaze to condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions.

New Wood: Remove mill glaze with sandpaper. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating. **Previously Painted Wood:** Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a tack or wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

Glossy Surfaces: For maximum adhesion, sand the surface thoroughly before coating.

Wood: WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Stain-blocking: After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before top-coating the entire area. If bleeding continues, a longer dry time of the primer may be needed before top-coating.

Masonry: All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using BEHR® Concrete & Masonry Cleaner & Etcher No. 991 or with mechanical means. Use BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 to remove loose aggregate and debris. Scrub vigorously into the surface with a plastic brush, broom, or power washer. Rinse thoroughly with water and allow drying.

Galvanized Metal, Metal & Aluminum: The oil film on new galvanized metal must be removed before it is painted. Remove oil film with a detergent and water solution. For better paint adhesion, sand the surface with sandpaper, steel wool, or by using BEHR® Concrete & Masonry Cleaner & Etcher No. 991. Clean by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Metal: Remove all rust and mill scale using sandpaper, steel wool, abrasive blasting, or other abrading methods to create a profile on the metal's surface. **New Surfaces:** Clean the metal by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be primed the same day it is cleaned.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

