



**PREMIUM PLUS WITH STYLE
FAUX GLAZE**

NO. 748

PRODUCT INFORMATION

This unique, water-based translucent product is designed for blending with BEHR PREMIUM PLUS ULTRA® or BEHR PREMIUM PLUS® Interior paints and applied using decorative paint applicators. This mixture extends the paint's open time allowing you to create dynamic faux-painted finishes and unique decorative wall designs.

RECOMMENDED USES:

Properly painted interior surfaces. Ideal for types of living and working spaces such as; Family Rooms, Living Rooms, Dining Rooms, Bedrooms, Kids' Rooms, Hallways, Kitchens, Bathrooms, Doors, Trim, Ceilings and offices.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. 748 Faux Glaze 128 oz

Sheen/Gloss: Not Applicable

Vehicle Type: Acrylic

***Weight Per Gallon:** 8.8 +/- 0.2 lbs./gal

***% Solids:**

By Volume: 20.5 +/- 2%

By Weight: 24.2 +/- 2%

VOC: <350 (g/l)

Flash Point: Not Applicable

Viscosity: 85-95 KU (un-tinted)

Recommended Film Thickness:

Wet: 4.0 Dry: 0.8 mils @ 400 SFPG

Coverage: Typical coverage is 400 sq. ft (37 m2) per gallon. Coverage may vary depending upon the surface and the desired effect.

Application:

Brush: Nylon/polyester

Roller: Use 3/8"-1/2" nap cover on smooth surfaces and 1/2"-3/4" on rough, porous surfaces.

Thinning: (If required) No more than 1/2 pint of water per gallon.

APPLICATION:

Remove loose paint, wash off any dirt and grease with detergent and remove mildew stains with BEHR® PREMIUM MOLD & MILDEW STAIN REMOVER NO. 62. Rinse and allow to dry. Scuff sand glossy surfaces. Countersink nailheads, repair imperfections and sand smooth. Remove all dust with a damp cloth and allow to dry. Allow new stucco, plaster and masonry to cure 30 days before priming. Use BEHR® ENAMEL UNDERCOATER PRIMER & SEALER NO. 75. Apply Interior Eggshell, Satin or Semi-Gloss sheen for the base color according to label instructions.

In a plastic container, blend 1 part paint (1 quart) to 4 parts glaze (1 gallon) for each selected glaze color. Stir glaze mixture until thoroughly blended and occasionally during application. Refer to the BEHR Faux Glazing Colors & Techniques Guide and www.behr.com for additional instructions on application. Using the appropriate tool and technique, apply the glaze color over the dried base color. Work in 3' x 3' (90 x 90 cm) areas or smaller depending on the technique. Blend from section to section in a random pattern and maintain a wet edge to ensure smooth transitions.

APPLICATION TOOLS:

Brush: Nylon/polyester

Roller: Use 3/8 nap cover

Air-less Spray: At packaged consistency

Tip: .015"

Filter: 60 mesh

Thinning: Do not thin



DRY TIME:

- 75°F (24°C) and 50% RH
- Dries to Touch 1 hour
- 4 hours before recoating

CLEAN UP:

Brushes and other equipment can be cleaned with warm, soapy water. For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

IMPORTANT! DO NOT OPEN CAN WITHOUT READING THESE INSTRUCTIONS.

This water-based translucent product is to be blended with BEHR PREMIUM PLUS® Interior paints. The paint and glaze mixture extends the paint's open time to allow you to create unique decorative wall designs.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





PREMIUM PLUS WITH STYLE FAUX GLAZE

NO. 748

SURFACE PREPARATION:

New Drywall: All drywall surfaces should be sufficiently sanded smooth. Remove any remaining drywall dust prior to priming. Allow all drywall compounds to be completely dry prior to coating.

Previously Painted Gypsum Board/Drywall: Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

Glossy Surfaces: For maximum adhesion, sand the surface thoroughly before coating.

New Plaster: New plaster should be thoroughly dried out and cured for a minimum of 30 days before painting. When cured, clean using a mixed solution of one part vinegar and one part water to remove efflorescence and neutralize.

Previously Painted Plaster: Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a tack or wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

Glossy Surfaces: For maximum adhesion, sand the surface thoroughly before coating.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

† WARNING! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

