



## PREMIUM PLUS WITH STYLE VENETIAN PLASTER TOP COAT

NO. 775

### PRODUCT INFORMATION

This 100% Acrylic, water-based, clear protective finish increases the durability and sheen of BEHR VENETIAN PLASTER.

### RECOMMENDED USES:

Apply after the VENETIAN PLASTER finish has completely dried at approximately 24 hours. Do not burnish the surface before or after the application of the VENETIAN PLASTER TOPCOAT.



### PRODUCT SPECIFICATIONS:

**Base:** No. 775.

**Sheen/Gloss:**

1.5-2.0 @ 20°  
10-15 @ 60°  
15-20 @ 85°

**Vehicle Type:** 100% Acrylic

**\*Weight Per Gallon:** 8.5 +/- 0.2 lbs./gal

**\*% Solids:**

By Volume: 23.2 +/- 2%  
By Weight: 29.2 +/- 2%

**VOC:** <275 (g/l)

**Flash Point:** Not Applicable

**Viscosity:** 120-130 KU

**Recommended Film Thickness:**

N/A – Can vary depending on the desired finish.

**Coverage:** Typical spread rate is 200 sq. ft. (19 m<sup>2</sup>) per quart.

**Application:**

**Tool:** Flexible steel trowel or drywall trowel

**Thinning:** DO NOT THIN

### APPLICATION:

Refer to the BEHR Faux Textures Colors & Techniques Guide and [www.behr.com](http://www.behr.com) for additional instructions on application. DO NOT THIN. Stir occasionally. Use product when the surface and air temperatures are between 50°-90°F (10°-32°C). Apply using a straight-edged, flexible steel trowel or wall scraper. Hold trowel at an angle and spread a very thin, even coat of the product across the surface. Remove any excess topcoat with a damp rag or sponge. The topcoat will dry to a Satin sheen and darken the tone and/or color of the finish.

### DRY TIME:

- 75°F (24°C) and 50% RH
- Dries to Touch 1 hour
- Cure: 24 hours

### CLEAN UP:

Brushes and other equipment can be cleaned with warm, soapy water. For disposal of empty containers and unused product, contact your household refuse collection service.

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

### SURFACE PREPARATION:

**New Drywall:** All drywall surfaces should be sufficiently sanded smooth. Remove any remaining drywall dust prior to priming. Allow all drywall compounds to be completely dry prior to coating.

**Previously Painted Gypsum Board/Drywall:** Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

**Glossy Surfaces:** For maximum adhesion, sand the surface thoroughly before coating.

**New Plaster:** New plaster should be thoroughly dried out and cured for a minimum of 30 days before painting. When cured, clean using a mixed solution of one part vinegar and one part water to remove efflorescence and neutralize.

**Previously Painted Plaster:** Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a tack or wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

**Glossy Surfaces:** For maximum adhesion, sand the surface thoroughly before coating.

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





## PREMIUM PLUS WITH STYLE VENETIAN PLASTER TOP COAT

NO. 775

**GENERAL INFORMATION:****IMPORTANT! DO NOT OPEN CAN WITHOUT READING**

**INSTRUCTIONS. WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED.**

**CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING.**

**USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

