



SOLID COLOR CONCRETE STAIN

NO. 800 WHITE



PRODUCT INFORMATION

BEHR® SOLID COLOR CONCRETE STAIN is a durable, water repellent, solid color stain. It is designed to help protect and enhance both interior and exterior, and vertical and horizontal, concrete surfaces. This silicized, 100% acrylic formula, forms a strong, long-lasting opaque film on properly prepared surfaces.

RECOMMENDED USES:

Use on properly prepared, interior or exterior surfaces, including: concrete, masonry walls, basements, patios, sidewalks, driveways*, garage floors*, tennis courts, cement blocks, pillars and brick. Do not use on surfaces subject to hydrostatic pressure. *Driveways and garage floors - Lack of proper surface preparation and/or excessive application can lead to automobile tires lifting the product from the surface.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

- *No. 800 White 124 oz / 6 oz
- No. 830 Deep Base 116 oz / 14 oz

Sheen: 5-10 @85°

Vehicle Type: Siliconized 100% Acrylic

***Weight per Gallon:** 10.0 +/- 0.2 lbs./gal

***% Solids:**

- By Volume: 28.9 +/- 2%
- By Weight: 40.5 +/- 2%

VOC: <100 g/l

Flash Point: Not Applicable

Viscosity: 60-80 KU

***Recommended Film Thickness:**

- Wet: 4.0 Dry: 1.2 mils @ 400 SFPG
- Wet: 2.7 Dry: 0.8 mils @ 600 SFPG

***Coverage:** 400-600 Square Feet Per Gallon depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: Use 1/4"-3/8" nap cover on smooth surfaces and 1/2"-3/4" on rough, porous surfaces.

Airless Spray: At packaged consistency

Tip: .015" - .017"

Filter: 60 mesh

Thinning: (If required) No more than 1/2 pint of water per gallon.

† Dry Time: @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

- † To Touch: 1 hour
- † To Recoat: 2-4 hours
- † Full Cure: 2 weeks

RECOMMENDED PRIMER / SYSTEMS:

New or uncoated Masonry:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

- Behr Concrete & Masonry Bonding Primer No. 880

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating. .
- Avoid heavy traffic for 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES		

CLEAN UP:

Clean all tools and equipment with soap and water. To recycle or dispose of paint, contact your household refuse collection service.

† WARNING! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





SOLID COLOR CONCRETE STAIN

NO. 800 WHITE

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust, and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow drying.

Mildew Stains: All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m²). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength. **Interior:** Use one part BEHR® Premium Mold & Mildew Stain Remover No. 62 to three parts water (1:3 dilution). **DO NOT USE FULL STRENGTH.** Avoid contact with clothing, carpet and fabrics. Apply using a clean cloth or sponge. Thoroughly rinse the surface with fresh water. Prolonged exposure on painted surfaces may damage finish.

Masonry: Stucco, Concrete, Cut Masonry Units (CMUs), Split-Faced Block: The oil film on new, galvanized metal must be removed before it is painted. Remove oil film with a detergent and water solution. For better paint adhesion, sand the surface with sandpaper, steel wool, or by using BEHR® Concrete & Masonry Cleaner & Etcher No. 991. Clean by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. **New Surfaces:** Wipe down clean metal surfaces prior to painting with a vinegar solution, one-part vinegar to five parts water (1:5). Bare metal must be primed the same day it is cleaned. Metal: Remove all rust and mill scale using sandpaper, steel wool, abrasive blasting, or other abrading methods to create a profile on the metal's surface. Clean the metal by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be coated the same day it is cleaned.

Masonry: Cement Composition Panels/Siding, Exterior Insulation and Finish Systems (EIFS) or Synthetic Stucco:

New: All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the substrate. **Previously Painted Surface:** All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow drying.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.

