

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



**BEHR®
INTERIOR/EXTERIOR
OIL-BASE HIGH-
GLOSS ENAMEL
PAINT NO. 8800
ULTRA PURE WHITE**

RECOMMENDED USES:

Properly prepared Interior or Exterior surfaces such as: Wood, Drywall, Plaster, Masonry, Metal, Well-bonded Wallpaper, Brick, Stucco, Aluminum and Cinder Block. Do not use on horizontal surfaces.

AVAILABLE IN: Quart & Gallon

COLORS

No. 8800 - Ultra Pure White

Tintable Bases/Max Tint

No. 8800 - Ultra Pure White
Ultra Pure White – 2 oz

Over 1600 custom colors plus computer color matching

FINISH

High-Gloss

*Gloss Level >88 @ 60°

*Substrate Dependant

COVERAGE RATE

500-550 sq. ft. (46-51 m²) per gallon over primed smooth surfaces and 350-400 sq. ft. (33-37 m²) per gallon over primed rough surfaces.
2.9 mils wet, 1.5 mils dry

DRYING TIME

@77°F & 50% humidity Longer dry time required in cooler temperatures and higher humidity.

To Touch: 4-5 Hours

Recoat: 24 Hours

Cured: 7 Days

PRIMERS

No. 436 Acrylic Primer & Sealer

No. 434 Oil-Based Primer & Sealer

COMPOSITION

Vehicle/Active Ingredient:

Alkyd Resins

Percent Solids By Volume:

52.0%

Percent Solids By Weight:

68.0%

Weight Per Gallon:

9.8 lbs.

VOC

379 g/l Material (Including Water)

379 g/l Coating (Excludes Water)

Flashpoint

104°F (40° C)

MSDS

Available @ www.behr.com

Or 1-800-854-0133 Ext. 2

Clean Up

Use mineral spirits. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

APPLICATION TOOLS

Airless Spray: Filter: 60 mesh Tip: .013 - .015

Conventional Spray: See manufacturer recommendations

Brush: High Quality China Bristle Brush

Roller: 1/4-3/8" Nap. Depending on the surface texture.

Thinner: Do Not Thin.

SURFACE PREPARATION

Allow new stucco, plaster and masonry to cure for 30 days. **CLEAN:** For interior and exterior surfaces, remove dirt, oil and grease stains with BEHR® No. 990 Concrete & Masonry Cleaner/Degreaser. To remove mildew stains, use BEHR No. 62 Premium Mildew Stain Remover. Remove all loose and peeling paint; scuff sand glossy surfaces; caulk; repair imperfections and sand smooth. For exterior surfaces, powerwash to remove chalk. Etch galvanized metal with BEHR No. 991 Concrete & Masonry Cleaner/Etcher. Follow all label instructions. **PRIME:** Use BEHR NO. 436 100% Acrylic Primer & Sealer or BEHR NO. 434 Oil-Based Primer & Sealer. Follow all label instructions.

APPLICATION

DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application & drying process. Certain colors may require more than one coat to achieve complete hide and coverage. Use product when air and surface temperatures are between 40–90°F (4–32°C).

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



**BEHR®
INTERIOR/EXTERIOR
OIL-BASED HIGH-
GLOSS ENAMEL
PAINT NO. 8830
DEEP BASE**

RECOMMENDED USES:

Properly prepared Interior or Exterior surfaces such as: Wood, Drywall, Plaster, Masonry, Metal, Well-bonded Wallpaper, Brick, Stucco, Aluminum and Cinder Block. Do not use on horizontal surfaces.

AVAILABLE IN: Quart & Gallon

COLORS

No. 8830 – Deep Base

Tintable Bases/Max Tint

No. 8830 - Deep Base
Deep Base - 14 oz

Over 1600 custom colors plus computer color matching

FINISH

High-Gloss
*Gloss Level >88 @ 60°
*Substrate Dependant

COVERAGE RATE

500-550 sq. ft. (46-51 m²) per gallon over primed smooth surfaces and 350-400 sq. ft. (33-37 m²) per gallon over primed rough surfaces.
2.9 mils wet, 1.5 mils dry

DRYING TIME

@77°F & 50% humidity Longer dry time required in cooler temperatures and higher humidity.

To Touch: 4-5 Hours
Recoat: 24 Hours
Cured: 7 Days

PRIMERS

No. 436 Acrylic Primer & Sealer
No. 434 Oil-Based Primer & Sealer

COMPOSITION

Vehicle/Active Ingredient:

Alkyd Resins

Percent Solids By Volume:

52%

Percent Solids By Weight:

61%

Weight Per Gallon:

8.2 lbs.

VOC

379 g/l Material (Including Water)
379 g/l Coating (Excludes Water)

Flashpoint

104°F (40° C)

MSDS

Available @ www.behr.com
Or 1-800-854-0133 Ext. 2

Clean Up

Use mineral spirits. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

APPLICATION TOOLS

Airless Spray: Filter: 60 mesh Tip: .013 - .015

Conventional Spray: See manufacturer recommendations

Brush: High Quality China Bristle Brush

Roller: 1/4-3/8" Nap. Depending on the surface texture.

Thinner: Do Not Thin.

SURFACE PREPARATION

Allow new stucco, plaster and masonry to cure for 30 days. **CLEAN:** For interior and exterior surfaces, remove dirt, oil and grease stains with BEHR® No. 990 Concrete & Masonry Cleaner/Degreaser. To remove mildew stains, use BEHR No. 62 Premium Mildew Stain Remover. Remove all loose and peeling paint; scuff sand glossy surfaces; caulk; repair imperfections and sand smooth. For exterior surfaces, powerwash to remove chalk. Etch galvanized metal with BEHR No. 991 Concrete & Masonry Cleaner/Etcher. Follow all label instructions. **PRIME:** Use BEHR NO. 436 100% Acrylic Primer & Sealer or BEHR NO. 434 Oil-Based Primer & Sealer. Follow all label instructions.

APPLICATION

DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application & drying process. Certain colors may require more than one coat to achieve complete hide and coverage. Use product when air and surface temperatures are between 40–90°F (4-32°C).

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



BEHR®
INTERIOR/EXTERIOR
OIL-BASED HIGH-
GLOSS ENAMEL
PAINT NO. 8850
PASTEL BASE

RECOMMENDED USES:

Properly prepared Interior or Exterior surfaces such as: Wood, Drywall, Plaster, Masonry, Metal, Well-bonded Wallpaper, Brick, Stucco, Aluminum and Cinder Block. Do not use on horizontal surfaces.

AVAILABLE IN: Quart & Gallon

COLORS

No. 8850 – Pastel Base

Tintable Bases/Max Tint

No. 8850 - Pastel Base
Pastel Base – 8 oz

Over 1600 custom colors plus computer color matching

FINISH

High-Gloss
*Gloss Level 45 - 55 @ 60°
*Substrate Dependant

COVERAGE RATE

500-550 sq. ft. (46-51 m²) per gallon over primed smooth surfaces and 350-400 sq. ft. (33-37 m²) per gallon over primed rough surfaces.
2.9 mils wet, 1.5 mils dry

DRYING TIME

@77°F & 50% humidity Longer dry time required in cooler temperatures and higher humidity.

To Touch: 4-5 Hours
Recoat: 24 Hours
Cured: 7 Days

PRIMERS

No. 436 Acrylic Primer & Sealer
No. 434 Oil-Based Primer & Sealer

COMPOSITION

Vehicle/Active Ingredient:

Alkyd Resins

Percent Solids By Volume:

52%

Percent Solids By Weight:

67%

Weight Per Gallon:

9.6 lbs.

VOC

379 g/l Material (Including Water)
379 g/l Coating (Excludes Water)

Flashpoint

104°F (40° C)

MSDS

Available @ www.behr.com
Or 1-800-854-0133 Ext. 2

Clean Up

Use mineral spirits. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

APPLICATION TOOLS

Airless Spray: Filter: 60 mesh Tip: .013 - .015

Conventional Spray: See manufacturer recommendations

Brush: High Quality China Bristle Brush

Roller: 1/4-3/8" Nap. Depending on the surface texture.

Thinner: Do Not Thin.

SURFACE PREPARATION

Allow new stucco, plaster and masonry to cure for 30 days. **CLEAN:** For interior and exterior surfaces, remove dirt, oil and grease stains with BEHR® No. 990 Concrete & Masonry Cleaner/Degreaser. To remove mildew stains, use BEHR No. 62 Premium Mildew Stain Remover. Remove all loose and peeling paint; scuff sand glossy surfaces; caulk; repair imperfections and sand smooth. For exterior surfaces, powerwash to remove chalk. Etch galvanized metal with BEHR No. 991 Concrete & Masonry Cleaner/Etcher. Follow all label instructions. **PRIME:** Use BEHR NO. 436 100% Acrylic Primer & Sealer or BEHR NO. 434 Oil-Based Primer & Sealer. Follow all label instructions.

APPLICATION

DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application & drying process. Certain colors may require more than one coat to achieve complete hide and coverage. Use product when air and surface temperatures are between 40–90°F (4-32°C).

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



**BEHR®
INTERIOR/EXTERIOR
OIL-BASED HIGH-
GLOSS ENAMEL
PAINT NO. 8860
ACCENT BASE**

RECOMMENDED USES:

Properly prepared Interior or Exterior surfaces such as: Wood, Drywall, Plaster, Masonry, Metal, Well-bonded Wallpaper, Brick, Stucco, Aluminum and Cinder Block. Do not use on horizontal surfaces.

AVAILABLE IN: Quart & Gallon

COLORS

No. 8860 – Accent Base

Tintable Bases/Max Tint

No. 8860 - Accent Base
Accent Base – 14 oz

Over 1600 custom colors plus computer color matching

FINISH

High-Gloss
*Gloss Level >88 @ 60°
*Substrate Dependant

COVERAGE RATE

500-550 sq. ft. (46-51 m²) per gallon over primed smooth surfaces and 350-400 sq. ft. (33-37 m²) per gallon over primed rough surfaces.
2.9 mils wet, 1.5 mils dry

DRYING TIME

@77°F & 50% humidity Longer dry time required in cooler temperatures and higher humidity.

To Touch: 4-5 Hours
Recoat: 24 Hours
Cured: 7 Days

PRIMERS

No. 436 Acrylic Primer & Sealer
No. 434 Oil-Based Primer & Sealer

COMPOSITION

Vehicle/Active Ingredient:

Alkyd Resins

Percent Solids By Volume:

52%

Percent Solids By Weight:

63%

Weight Per Gallon:

8.6 lbs.

VOC

379 g/l Material (Including Water)
3790 g/l Coating (Excludes Water)

Flashpoint

104°F (40° C)

MSDS

Available @ www.behr.com
Or 1-800-854-0133 Ext. 2

Clean Up

Use mineral spirits. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

APPLICATION TOOLS

Airless Spray: Filter: 60 mesh Tip: .013 - .015

Conventional Spray: See manufacturer recommendations

Brush: High Quality China Bristle Brush

Roller: 1/4-3/8" Nap. Depending on the surface texture.

Thinner: Do Not Thin.

SURFACE PREPARATION

Allow new stucco, plaster and masonry to cure for 30 days. **CLEAN:** For interior and exterior surfaces, remove dirt, oil and grease stains with BEHR® No. 990 Concrete & Masonry Cleaner/Degreaser. To remove mildew stains, use BEHR No. 62 Premium Mildew Stain Remover. Remove all loose and peeling paint; scuff sand glossy surfaces; caulk; repair imperfections and sand smooth. For exterior surfaces, powerwash to remove chalk. Etch galvanized metal with BEHR No. 991 Concrete & Masonry Cleaner/Etcher. Follow all label instructions. **PRIME:** Use BEHR NO. 436 100% Acrylic Primer & Sealer or BEHR NO. 434 Oil-Based Primer & Sealer. Follow all label instructions.

APPLICATION

DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application & drying process. Certain colors may require more than one coat to achieve complete hide and coverage. Use product when air and surface temperatures are between 40–90°F (4-32°C).

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2