



1-PART EPOXY ACRYLIC CONCRETE & GARAGE FLOOR PAINT

NO. 900



PRODUCT INFORMATION

A high-performance, ready-to-use, single component water-based floor paint that resists hot tire pick-up and marring. The finish is resistant to household type chemicals, oil and gasoline, which reduces the need for maintenance of hard-to-clean interior or exterior floors. This durable, satin finish floor paint also resists scuffing, fading, cracking, peeling and blistering.

RECOMMENDED USES:

Interior or Exterior surfaces such as: Porous Concrete, Masonry, Stone and Brick. Ideal for horizontal surfaces such as: Garage Floors, Driveways, Basements and Porches. DO NOT use on vertical surfaces or areas subject to hydrostatic pressure. NOT for industrial use. DO NOT use on areas subject to fork-lifts.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

- *No. 900 White Base 122 oz. / 8 oz.
- No. 2-900 White Base 122 oz. / 8 oz.
- No. 930 Deep Base 116 oz. / 14 oz.
- No. 2-930 Deep Base 116 oz. / 14 oz.

PRE-MIXED COLORS:

- No. 901 Silver Gray
- No. 902 Slate Gray

Sheen:

- 15-25 @ 60°
- 40-60 @ 85°

Vehicle Type: Epoxy/Acrylic

*Weight Per Gallon: 9.7 +/- 0.2 lbs./gal

*% Solids:

- By Volume: 30.0 +/- 2%
- By Weight: 39.7 +/- 2%

VOC: No. 900: <250 (g/l)

No. 2-900: <100 (g/l)

Flash Point: Not Applicable

Viscosity: 90-100 KU

*Recommended Film Thickness:

- Wet: 5.3 Dry: 1.6 mils @ 300 SFPG
- Wet: 3.2 Dry: 1.0 mils @ 500 SFPG

*Coverage: 300-500 Square Feet Per Gallon, depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION

DO NOT THIN. Intermix all cans of same product to ensure color uniformity. Stir before applying. Use product when air and surface temperatures are between 50°-90°F (10°-32°C). Apply a thin, even coat using a 3/8" nap roller cover, pad applicator or a nylon/polyester brush at a spread rate of 400-500 sq. ft. (37-46 m²) per gallon on smooth surfaces and 300-400 sq. ft. (28-37 m²) per gallon on rough surfaces. Allow first coat to dry 24 hours before deciding if a second coat is necessary. For uniformity apply a second coat (in a criss-cross direction). Airless spray is recommended for experienced applicators only. An annual touch-up may be required in areas subject to tire traffic.

APPLICATION TOOLS:

Brush: Nylon/polyester

Roller: Use 3/8"-1/2" nap cover on smooth surfaces and 1/2"-3/4" on rough, porous surfaces.

Air-less Spray: At packaged consistency

Tip: .015" - .019"

Filter: 60 mesh

Thinning: DO NOT THIN

Dry Time: @ 77° & 50% RH

Dries to the touch in 2 hour.

4 hours before recoating.

Allow surface to dry 24-48 hours before

subjecting surface to heavy foot traffic.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- DO NOT APPLY MORE THAN TWO COATS
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Brushes and other equipment can be cleaned with warm, soapy water. For disposal of empty containers and unused product, contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

COMPLIES WITH THE BELOW AS OF 3/22/2011			
OTC	YES	CARB	YES
SCAQMD	YES		

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





1-PART EPOXY ACRYLIC CONCRETE & GARAGE FLOOR PAINT

NO. 900

SURFACE PREPARATION:

Mildew Stains: All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m²). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI).

New and Uncoated Concrete or Masonry Surfaces:

New concrete must cure for a minimum of 30 days. For proper penetration and adhesion of topcoat, use BEHR® Concrete & Masonry Cleaner & Etcher No. 991 to clean and etch the surface. Follow all label instructions. Apply BEHR® Concrete & Masonry Bonding Primer No. 880 to increase adhesion of topcoat to the surface. Follow all label instructions.

Painted, Stained or Sealed Concrete:

Option 1- To completely strip the entire surface, use BEHR® Concrete & Masonry Paint Stripper No. 992. Follow all label instructions.

Option 2- To recoat over an existing coating, remove any loose or peeling paint and scuff sand the surface. Use BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 to clean previously coated surfaces in sound condition. Use BEHR® Concrete & Masonry Cleaner & Etcher No. 991 to clean and etch any bare concrete area. Follow all label instructions. Spot prime all bare concrete areas with BEHR® Concrete & Masonry Bonding Primer No. 880 to increase adhesion of topcoat to the surface. Follow all label instructions.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

