

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or [www.behr.com](http://www.behr.com)



**BEHR®  
CONCRETE &  
MASONRY  
WATERPROOFER  
No. 980**

### **RECOMMENDED USES:**

*Horizontal and Vertical porous Concrete and Masonry surfaces such as: Concrete Block, Pavers, Stucco, Brick, Unglazed Tiles, Exposed Aggregate Concrete, Sandstone and Slate. **Not recommended** for use on areas subject to hydrostatic pressure such as basement walls or floors.*

**AVAILABLE IN:** Gallon & Five Gallon

### **COLORS**

No. 980 Clear

### **Tintable Bases/Max Tint**

No. 980 – 128 oz.\*

\*Not Tintable

### **FINISH**

N/A

### **COVERAGE RATE**

250 sq. ft. per gallon.

### **DRYING TIME**

@77°F & 50% humidity\*

\*Longer dry time required in cooler temperatures or in higher humidity.

Dry: 24-48 Hours

Once dried, rough, vertical surfaces may be coated with an oil or latex-based paint or primer. Follow all label instructions. **Do not** paint horizontal surfaces after applying this product

### **PRIMERS**

N/A

### **COMPOSITION**

#### **Vehicle/Active Ingredient:**

Silicone Resins

#### **Percent Solids By Volume:**

10%

#### **Percent Solids By Weight:**

8%

#### **Weight Per Gallon:**

8.2 lbs.

### **VOC**

1gm/l Material (Includes Water)

12 gm/l Coating (Excludes Water)

### **Flashpoint**

N/A

### **MSDS**

Available @ [www.behr.com](http://www.behr.com)

Or 1-800-854-0133 Ext. 2

### **Clean Up**

Soap & Water. Recycle or dispose of paint call 1-800-CLEANUP (U.S.A. only) [www.earth911.org](http://www.earth911.org)

### **APPLICATION TOOLS**

**Airless Spray:** Filter: 100 mesh Tip: .013-.015

**Conventional Spray:** See manufacturer recommendations

**Pump Sprayer:** High Quality with Adjustable tip.

**Brush:** Nylon/Polyester blend or Pad Applicator

**Roller:** 1/4"-3/8" Nap. Depending on the surface texture.

**Thinner:** Do Not Thin.

### **SURFACE PREPARATION**

New concrete must cure for a minimum of 30 days. Remove Old Coating, if present, for proper penetration and adhesion. **CLEAN:** Remove dirt, oil and grease stains with BEHR® No. 990 Concrete Cleaner & Degreaser. For mildew stain removal, use BEHR No. 62 Multi-Surface Cleaner & Mildew Stain Remover or bleach and water. Follow all label instructions. **TEST:** Sprinkle a few drops of water onto the surface. If water is quickly absorbed, the surface is ready. If not absorbed, etc. **ETCH:** For smooth or new concrete, or for surfaces with efflorescence, use BEHR No. 991 Concrete Etcher & Rust Remover. Follow all label instructions.

### **APPLICATION**

Stir or shake before applying. Use product when temperature is between 50–90°F (10-32°C). Apply until saturated by brush, roller or garden sprayer to a dry surface. Remove any puddles by spreading product to drier areas or by wiping up excess with a clean cloth. On vertical surfaces, apply from the bottom up and saturate well.

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

**To Consult with a Technical Service Representative call  
1-800-854-0133 Ext. 2**