



WET-LOOK SEALER

NO. 985 HIGH GLOSS & NO. 986 LOW LUSTRE



PRODUCT INFORMATION

BEHR® WET-LOOK SEALER's are a clear, non-yellowing, high solids, acrylic-based masonry sealer. It is formulated to seal, protect and beautify concrete and masonry surfaces with a high gloss, wet-look finish. BEHR WET-LOOK SEALER NO. 985 is also an excellent topcoat for paints and stains.

RECOMMENDED USES:

Use on Previously Coated or Uncoated, Vertical or Horizontal, Interior or Exterior surfaces such as: pavers, concrete, mexican tile and unglazed tiles, brick, aggregate, natural and artificial stone, masonry and stucco. Not recommended for use on wood, metal, granite, marble, terrazzo, areas immediately adjacent to pools or areas subject to hydrostatic pressure. Do not use over oil-based products. **CAUTION:** Sealed surfaces may become slippery when wet. Use caution when walking on surface when moisture is present. Apply in sections so wet material does not have to be walked on during application.

PRODUCT SPECIFICATIONS:

Bases:

- *No. 985 Wet Look High Gloss 128 oz
- No. 986 Wet Look Low Lustre 128 oz

Vehicle Type: Acrylic

***Weight per Gallon:** 8.5 +/- 0.2 lbs./gal

***% Solids:**

- By Volume: 30.5 +/- 2%
- By Weight: 32.9 +/- 2%

VOC: <100 g/l

Flash Point: Not Applicable

Viscosity: 20-35 sec, #2 Zahn Cup

***Recommended Film Thickness:**

- Wet: 8.0 Dry: 2.4 mils @ 200 SFPG
- Wet: 2.3 Dry: 0.7 mils @ 700 SFPG

***Coverage:** 200-700 Square Feet Per Gallon, depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

DO NOT THIN. Stir or shake before applying. Use product when temperature is between 50-80°F (10-27°C). Do not apply in direct sunlight. Do not apply to wet surfaces or if rain or heavy dew is expected within 24 hours. Apply a thin coat using a nylon/polyester brush, 3/8-1/2" nap roller or a high quality pump sprayer with an adjustable tip at a spread rate of 150-300 sq. ft. (14-28 m²) per gallon. Spread rate is highly dependent on surface roughness and porosity. If sprayed, backroll for uniform thickness. Allow first coat to dry 4 hours, then apply a second coat at a spread rate of 300-400 sq. ft. (28-37 m²) per gallon. Additional coats (no more than 4) may be added for a higher gloss and added protection. Note: Horizontal surfaces may be subject to excessive wear. Therefore, periodic touch-ups may be necessary.

APPLICATION TOOLS:

- Brush:** Nylon/polyester
- Roller:** Use 3/8"-1/2" nap cover on smooth surfaces and 1/2"-3/4" on rough, porous surfaces.
- Air-less Spray:** At packaged consistency.
- Tip:** .015"
- Filter:** 60 mesh
- Thinning:** DO NOT THIN
- Dry Time:** @ 77° & 50% RH
 - Dries to the touch in 1 hour.
 - 4 hours before recoating.
 - Allow surface to dry 24-48 hours before subjecting surface to heavy foot traffic.

COMPLIES WITH THE BELOW AS OF 3/22/2011			
OTC	YES	CARB	YES
SCAQMD	YES	MPI #	99

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24-48 hours.
- Allow 72 hours before repositioning furniture
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Brushes and other equipment can be cleaned with warm, soapy water. For disposal of empty containers and unused product, contact your household refuse collection service.

† WARNING! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





WET-LOOK SEALER

NO. 985 HIGH GLOSS & NO. 986 LOW LUSTRE

SURFACE PREPARATION:

Mildew Stains: All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m²). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength.

Masonry: Concrete, Cut Masonry Units (CMUs), Split-Faced Block: New and Uncoated: All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using BEHR® Concrete & Masonry Cleaner & Etcher No. 991 or with mechanical means. Remove loose aggregate and debris using BEHR® Concrete & Masonry Degreaser & Cleaner No. 990. Scrub vigorously into the surface with a plastic brush broom or power washer. Rinse thoroughly with water and allow to dry.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING: IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

