

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



BEHR®
INTERIOR/EXTERIOR
LOW-LUSTRE SEALER
No. 986

RECOMMENDED USES: Use on previously Coated or Uncoated, Vertical or Horizontal, Interior or Exterior surfaces such as: Pavers, Concrete, Mexican Tile and Unglazed Tiles, Brick, Aggregate, Natural and Artificial Stone, Masonry and Stucco. Not recommended for use on wood, metal, granite, marble, terrazzo, areas immediately adjacent to pools or areas subject to hydrostatic pressure. Do not use over Oil-Based products.

AVAILABLE IN: Gallon Only

COLORS

No. 985 Clear Hi-Gloss

Tintable Bases/Max Tint

NOT TINTABLE

FINISH

Hi-Gloss.

*Gloss Level 75.0-100.0 @ 60°

*Substrate Dependant

COVERAGE RATE

First Coat: 150-300 sq. ft. (14-28 m²) per gallon. Second Coat: 300-400 sq. ft. (28-37 m²) per gallon. 5.3 mils wet, 1.6 mils dry

DRYING TIME

@77°F & 50% humidity*

*Longer dry time may be needed in cooler temperatures or in higher humidity.

Park tires on corrugated cardboard for 14 days after applying product. Wait at least 30 days before cleaning with a mild, non-abrasive liquid detergent.

To Touch: 1 Hour

Recoat: 4 Hours

Light Foot Traffic: 24 Hours

Repositioning Furniture: 72 Hours

Tire Traffic: Two Weeks

Cured: 30 Days

PRIMERS

N/A

COMPOSITION

Vehicle/Active Ingredient:

100% Acrylic

Percent Solids By Volume:

30.0%

Percent Solids By Weight:

32.4%

Weight Per Gallon:

8.54 lbs.

VOC

32 gm/l Material (Includes Water)

96 gm/l Coating (Excludes Water)

Flashpoint

N/A

MSDS

Available @ www.behr.com

Or 1-800-854-0133 Ext. 2

Clean Up

Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of product in your community call 1-800-CLEANUP or visit www.Earth911.org.

CAUTION Sealed surfaces may become slippery when wet. Use caution when walking on surface when moisture is present. Apply in sections so wet material does not have to be walked on during application.

APPLICATION TOOLS

Airless Spray: N/A

Conventional Spray: See manufacturer recommendations

Pump Sprayer: High quality pump sprayer with an adjustable tip.

Brush: Nylon/Polyester blend

Roller: 3/8"-1/2" Nap. Depending on the surface texture.

Thinner: Do Not Thin.

SURFACE PREPARATION

New concrete must cure for a minimum of 30 days. For proper penetration and adhesion of sealer on new or smooth concrete floors, use BEHR® No. 991 Concrete & Masonry Cleaner/Etcher to clean and etch the surface. Follow all label instructions. Use BEHR No. 990 Concrete & Masonry Cleaner/Degreaser to clean previously coated surface in sound condition. Scrape and remove any loose or peeling coating. To completely strip the surface use BEHR No. 992 Concrete & Masonry Paint Stripper. Follow all label instructions. Scrape and remove any loose or peeling coating.

APPLICATION

DO NOT THIN. Stir or shake before applying. Use product when temperature is between 50-80°F (10-27°C). Do not apply in direct sunlight. Do not apply to wet surfaces or if rain or heavy dew is expected within 24 hours. If sprayed, backroll for uniform thickness. Additional coats (no more than 4) may be added for a higher gloss and added protection. **NOTE: Horizontal surfaces may be subject to excessive wear. Therefore, periodic touch-ups may be necessary.**

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2