



PREMIUM DECK, FENCE & SIDING MOLD & MILDEW STAIN REMOVER

NO. 62

PRODUCT INFORMATION

An interior/exterior cleaner formulated to remove stains caused by mold, mildew, algae and fungus. It cleans dirt and stains while lightening old, weathered wood. Removes mildew stains quickly and easily. This product is ready-to-use with no mixing required and is easy to clean up... just use water.

RECOMMENDED USES:

INTERIOR: Use on, Interior Mildew-Stained Surfaces, Bathroom and Kitchen areas, and Woodwork. EXTERIOR: Use on stains caused by mold, mildew, algae & fungus. Does not contain bleach and will not damage wood surfaces. Use full strength on: Exterior Mildew-Stained Surfaces of all types including Wood, Concrete, Masonry, Stucco, Stone, Brick, Vinyl and Aluminum Siding, Composite, Tile, Plastic, Fiberglass and Roofing materials. Use BEHR® PREMIUM 2-IN-1 WOOD PREP NO. 63 after application to remove mill glaze, condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions.

PRODUCT SPECIFICATIONS:

No. 62 128 oz

*Weight per Gallon: 8.4 +/- 0.2 lbs./gal

*% Solids: By Weight: Not Applicable

VOC: 0 (g/l)

Flash Point: Not Applicable

Viscosity: Water thin

SURFACE PREPARATION:

To remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood decks, siding, fences, shakes and shingles use BEHR® PREMIUM STAIN & FINISH STRIPPER NO. 64.

Use BEHR PREMIUM 2-IN-1 WOOD PREP NO. 63 to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae & fungus. Rinse thoroughly. Allow to dry. Apply coating. On new wood use NO. 63 to remove mill glaze and open the pores of the wood. For severe stains caused by mold, mildew, algae & fungus apply BEHR PREMIUM MOLD & MILDEW STAIN REMOVER NO. 62 and rinse prior to applying BEHR PREMIUM 2-IN-1 WOOD PREP NO. 63.

APPLICATION:

EXTERIOR: Use product at full strength. Apply using a pump sprayer, brush, mop, or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of product will treat 200-250 sq. ft. (19-23 m2). Allow product to work for at least one minute to remove mildew stains. Do not allow product to dry on surface. Rinse surface and surrounding area thoroughly with water from garden hose using nozzle at normal pressure, or use pressure washer at low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm wood. Prolonged exposure on painted surfaces may damage finish.

INTERIOR: Product must be diluted with one part BEHR® PREMIUM MOLD & MILDEW STAIN REMOVER NO. 62 to three parts water (1:3 dilution). DO NOT USE FULL STRENGTH.

Avoid contact with clothing, carpet and fabrics. Apply using a clean cloth or sponge. Thoroughly rinse the surface with fresh water. Prolonged exposure on painted surface may damage finish.

CLEAN UP:

Biodegradable. Rinse all equipment with water before storage or reuse. Clean with soap & water. Properly dispose of all soiled rags and protect unused product from freezing. For disposal of unused paint products, please contact your household refuse collection service.



CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- **CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

Wood: WARNING! Sanding or scraping pressure treated

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





PREMIUM DECK, FENCE & SIDING MOLD & MILDEW STAIN REMOVER

NO. 62

lumber may be hazardous; wear appropriate protection.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

CAUTION. IRRITANT. MAY CAUSE EYE AND SKIN IRRITATION. PROLONGED INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED.

FIRST AID: In case of eye or skin contact, flush immediately with water for 20 minutes. For respiratory tract irritation, remove to fresh air.

In case of ingestion, do not induce vomiting. Drink plenty of water and get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



PREMIUM 2-IN-1 WOOD PREP

NO. 63

PRODUCT INFORMATION

Specifically formulated to clean, brighten and condition exterior wood surfaces prior to applying natural finishes, paints or stains..

RECOMMENDED USES:

Exterior Wood & Composites, Siding, Shakes, Shingles, Fences and Patio Furniture, Vinyl and Aluminum Siding, Masonry, Stucco and Concrete. Brightens and conditions exterior wood. Removes stains caused by mold, mildew, algae and fungus. Removes mill glaze, tannin bleed, rust & red clay stains. Removes household stains such as BBQ Sauce, Ketchup, Wine, etc. Neutralizes wood surface to restore natural color. Use after BEHR® NO. 62 PREMIUM MOLD & MILDEW STAIN REMOVER for best results on wood. Must be applied after BEHR® NO. 64 PREMIUM STAIN & FINISH STRIPPER when removal of old finish is required. Use BEHR® NO. 63 PREMIUM 2-IN-1 WOOD PREP after application of BEHR® NO. 64 PREMIUM STAIN & FINISH STRIPPER to remove mill glaze, condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions.



PRODUCT SPECIFICATIONS:

No. 63 128 oz

***Weight per Gallon:**

8.7 +/- 0.2 lbs./gal

***% Solids:**

By Weight: 13.4 +/- 2%

VOC (C.O.V.): <1 wt %

Flash Point: Not Applicable

Viscosity: Not Applicable

SURFACE PREPARATION:

Be sure to have the following: source for tap water, garden hose with nozzle, large plastic mixing container, stiff bristle broom or brush and protective plastic drop cloths. Wear protective clothing, goggles, and acid resistant gloves. Use BEHR® PREMIUM MOLD & MILDEW STAIN REMOVER NO. 62 where severe stains caused by mold, mildew, algae, or fungus are present and cannot be removed with BEHR® PREMIUM 2-IN-1 WOOD PREP NO. 63. Follow all label instructions. Prevent all rinse solution from entering storm drains.

APPLICATION:

Shake product thoroughly.

Be sure that the plastic mixing container is large enough to hold up to 5 gallons of diluted solution. **DO NOT MIX IN METAL CONTAINER.**

Dilute one part BEHR® PREMIUM 2-IN-1 WOOD PREP NO. 63 with 4 parts tap water (1:4 dilution) in a clean plastic container. One gallon of diluted solution will clean, brighten and condition up to 200 sq. ft. (19 m²). For best results on wood surfaces prone to tannin bleed, such as redwood and cedar, use a 1:1 diluted solution. To remove rust, red clay stains and for extremely hard to clean weathered wood surfaces, use product full strength. Test solution in a small, hidden area before applying to see its effectiveness. Do not apply product if surface and air temperatures are below 50°F (10°C) or above 90°F (32°C). Dampen surfaces with water prior to cleaning. Apply solution liberally with a plastic container pump sprayer, brush, mop or roller. Keep the surface wet for 10-15 minutes.

Re-apply solution as needed to keep the surface wet. Scrub surface using a stiff bristle broom or brush. The solution will foam. After the 10-15 minute cleaning period, rinse thoroughly with water from garden hose at normal pressure, or use a pressure washer at low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm the wood. Surfaces other than wood may be dulled if not rinsed off quickly. On new wood use NO. 63 to remove mill glaze and open the pores of the wood.

CLEAN UP:

Biodegradable. Rinse all equipment thoroughly with water before storage or reuse. Clean with soap and water. Properly dispose of all soiled rags and protect unused product from freezing. For disposal of unused paint products, please contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. **NOTE:** If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- **CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

Wood: WARNING! Sanding or scraping pressure treated lumber may be hazardous;

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





PREMIUM 2-IN-1 WOOD PREP

NO. 63

wear appropriate protection.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

DANGER! CORROSIVE. WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS OXALIC ACID SOLUTION (LESS THAN 10%). MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION.

NOTICE: Do not mix BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP with chlorine bleach or with any other household or industrial cleaning product or detergent. Mix only in plastic containers. Use with adequate ventilation. Only use this product outdoors. Avoid contact with skin. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection.

FIRST AID: Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth

defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



PREMIUM DECK, FENCE & SIDING STAIN & FINISH STRIPPER

NO. 64

PRODUCT INFORMATION

A ready-to-use exterior stripper designed to rapidly remove oil, latex-based, and 100% acrylic finishes such as semi-transparent stains, solid color stains and clear sealers. It also removes loose wood fibers to help ensure a sound surface prior to staining or painting. Created especially for use on deck and siding surfaces, it removes previous coatings from wood, tile, concrete, masonry, stucco, stone and brick.

RECOMMENDED USES:

Exterior latex, oil-based and 100% acrylic coatings on Wood Decks, Siding, Fences, Shakes and Shingles. Removes loose wood fibers without sanding. Ideal for unsightly stains caused by oil or rusty water on uncoated Tile, Concrete, Masonry, Stucco, Stone, and Brick. Not for interior use or on aluminum surfaces. May harm bare metal or painted surfaces.

PRODUCT SPECIFICATIONS:

No. 64 128 oz

Active Type: Sodium Hydroxide

***Weight per Gallon:** 8.9 +/- 0.2 lbs./gal

***% Solids:** By Weight: 11.5 +/- 2%

VOC (C.O.V.): 3.4 wt %

Flash Point: Not Applicable

Viscosity: Not Applicable

SURFACE PREPARATION:

STIR OR SHAKE WELL BEFORE OPENING. DO NOT THIN PRODUCT. Be sure to have the following: source for tap water, garden hose with nozzle, plastic sprayer or disposable brush, stiff bristle broom or brush and BEHR® PREMIUM 2-IN-1 WOOD PREP NO. 63. Surface must be dry. Do not apply in direct sunlight or on hot surfaces. Use product when air and surface temperatures are between 50°-90°F (10°-32°C). Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Wear protective clothing, goggles, chemical-resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge. Test in a small area for effectiveness, rinse and let dry before continuing. Prevent all rinse solution from entering storm drains.

APPLICATION:

Apply BEHR® PREMIUM STAIN & FINISH STRIPPER NO. 64 liberally using a nylon/poly brush or roller. Natural bristle brushes or lambs wool applicators are not recommended. Due to the viscosity or thickness of this product, DO NOT APPLY WITH A PUMP SPRAYER. Do not allow product to dry on wood; keep surface wet by misting with water and re-apply BEHR® PREMIUM STAIN & FINISH STRIPPER NO. 64 if drying occurs. Finish will begin to lift from the surface. Repeat process as needed to keep the surface wet during the removal period. Most deteriorated finishes will start to lift after about 5-45 minutes. The coating should easily rinse off when ready. When the finish starts to lift, lightly scrub the surface using a stiff bristle broom or brush. Rinse thoroughly with water from garden hose using nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. If some of the old finish remains on the surface, repeat application procedure or spot sand as needed. Use at a rate of approximately 50-150 sq. ft. (4-14m²) per gallon, depending on porosity and condition of surface. Some woods may darken after stripping. Use BEHR PREMIUM 2-IN-1 WOOD PREP NO. 63 on all wood surfaces to remove stains caused by mold & mildew, rejuvenate natural wood color and neutralize the stripping action. Follow all label instructions. This provides stability for reapplication of a new finish or sealer.

CLEAN UP:

Biodegradable. Rinse all equipment with water before storage or reuse. Clean with soap & water. Properly dispose of all soiled rags and protect unused product from freezing. For disposal of unused paint products, please contact your household refuse collection service.



DRY TIME:

Before applying a coating, allow the wood to dry for a minimum of 24 hours in warm, dry weather or longer in cool temperatures and/or high humidity. Surfaces must be thoroughly dry before applying any type of new finish, except those finishes that can be applied to dampened wood.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- **CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

Wood: WARNING! Sanding or scraping pressure treated

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





PREMIUM DECK, FENCE & SIDING STAIN & FINISH STRIPPER

NO. 64

Lumber may be hazardous; wear appropriate protection.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

DANGER! CORROSIVE. WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS SODIUM HYDROXIDE. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION.

USE ONLY WITH ADEQUATE VENTILATION. Only use this product outdoors. Avoid contact with skin. Wear protective clothing, acid resistant rubber gloves and eye goggles. If properly used, a respirator may offer additional protection.

FIRST AID: Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



CONCRETE & MASONRY DEGREASER & CLEANER

NO. 990



PRODUCT INFORMATION

Extremely effective when used full strength to remove greasy, oily stains such as transmission fluid and anti-freeze caused by automobiles, motorcycles and bicycles. Use a diluted solution on lightly stained and soiled areas. Ideal for removing mildew stains, dirt and most fluids from concrete surfaces.

RECOMMENDED USES:

Use on Interior/Exterior surfaces such as: Garage Floors, Driveways, Patios, Walkways, Porches, Basement Floors and Pool Decks. Great on Concrete, Brick, Stone, Asphalt and Exposed Aggregate.

PRODUCT SPECIFICATIONS:

No. 990 128 oz

Actives: Citrus/Alkali

***Weight per Gallon:** 9.0 +/- 0.2 lbs./gal

***% Solids:**

By Weight: 17.2 +/- 2%

VOC (C.O.V.): 3.7 wt %

Flash Point: Not Applicable

Viscosity: Not Applicable

APPLICATION:

Mixing: Do not mix BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 with bleach, household or industrial cleaning products or detergents. Mix only in plastic containers.

DO NOT MIX IN A METAL CONTAINER. Use a plastic mixing container, large enough to hold up to 5 gallons of diluted solution. Use BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 full strength for tough stains. For general cleaning, add 1 quart cleaner in 1 gallon of water (1:4 dilution). For cleaning previously painted surfaces, add 1 cup cleaner in 1 gallon of water (1:16 dilution). Stir diluted solution thoroughly. Avoid splashing. Wear protective clothing, goggles and acid resistant rubber gloves & boots. One gallon of diluted solution will clean and degrease up to 500 sq. ft. (47 m²) and one gallon of full strength will cover 150 sq. ft. (14 m²). Actual coverage will depend on method of application, texture and surface porosity. Wet the surface first by spraying with a garden hose. Then apply the product (full strength for tough stains, diluted for general cleaning) and work into the surface with a stiff bristled, non-metal brush or broom. For best results, use a plastic watering can or plastic pump sprayer to evenly distribute product. Allow product to stand for 10-20 minutes then scrub vigorously. NOTE: Heavily stained areas or older stains may require an additional application. After application, be sure to thoroughly saturate surrounding grass and plants with fresh water. Rinse surface thoroughly with fresh water while scrubbing at the same time to properly remove all remaining residue. Pressure wash for best results. Remove excess water with a non-metal squeegee or mop.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Thoroughly rinse all surfaces, clothing and tools with fresh water after use.

If product accidentally comes in contact with painted or finished surfaces, rinse immediately with fresh water. It will damage automobile finishes if not rinsed. For disposal of unused paint products, please contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

SURFACE PREPARATION:

Wipe up all excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on surface. Test Patch: Conduct a small test patch in an inconspicuous area to ensure product performance. Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Prevent all rinse solution from entering storm drains.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

DANGER! CORROSIVE! WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS POTASSIUM HYDROXIDE. AVOID CONTACT WITH SKIN. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.



CONCRETE & MASONRY CLEANER & ETCHER NO. 991 BIODEGRADABLE & EASY WATER CLEAN-UP



PRODUCT INFORMATION

BEHR CONCRETE & MASONRY CLEANER & ETCHER is part of the BEHR family of Concrete & Masonry Prep products. It is an interior/ exterior, 2-in-1 cleaner and etcher specifically formulated to prepare the surface prior to coating. It is designed to clean and etch bare concrete and masonry surfaces to improve penetration and adhesion of paints, stains and sealers. This biodegradable and easy water clean-up product will remove grease, oil, auto fluids, rust and red clay stains from any concrete and masonry surface. BEHR NO. 991 is ideal for use on uncoated surfaces such as: garage floors, driveways, walkways, patios, basement floors and walls.

RECOMMENDED USES:

Use on Interior/Exterior uncoated surfaces such as: garage floors, driveways, walkways, patios, basement floors and concrete walls. Removes grease, oil, auto fluids, rust and red clay stains. **DO NOT USE ON MARBLE, GRANITE, TERRAZZO, COLORED CONCRETE, BRASS, BRONZE or COPPER.** NOTE: If etching is not desired, use BEHR® CONCRETE & MASONRY DEGREASER & CLEANER NO. 990.

PRODUCT SPECIFICATIONS:

- No. 991** 128 oz
- Actives:** Organic Salt
- *Weight per Gallon:** 9.1 +/- 0.2 lbs./gal
- *% Solids:**
 - By Weight: 30.6 +/- 2%
- VOC (C.O.V.):** 0 wt %
- Flash Point:** Not Applicable
- Viscosity:** Water-thin

APPLICATION:

Mixing: DO NOT MIX IN A METAL CONTAINER. Use a plastic mixing container, large enough to hold up to 2 gallons of diluted solution. Use full strength on hard to clean interior/ exterior stained surfaces and smooth concrete. Always work in a well-ventilated area. For new and lightly stained concrete or to etch galvanized metal, use a diluted solution of 1 part BEHR® Concrete & Masonry Cleaner & Etcher No. 991 to 1 part water (1:1 dilution). Stir diluted solution thoroughly. Avoid splashing. Wear protective clothing, goggles and acid resistant rubber gloves & boots. Avoid splashing. Spraying is not recommended. One gallon of full strength product will etch and clean 150-200 sq. ft. (14-18 m²). One gallon of diluted solution will etch and clean 300-400 sq. ft. (28-37 m²). Actual coverage depends on porosity and severity of surface. For best results, use a plastic watering can to evenly distribute product or spread product using a stiff bristled, non-metal brush or broom. On sloped surfaces, start at the lowest point working up to the highest point. Apply BEHR® Concrete & Masonry Cleaner & Etcher No. 991 to a dry surface for best results. Allow product to stand for 10-20 minutes then scrub vigorously. Do not let product dry on the surface. Rinse surface thoroughly with fresh water while scrubbing at the same time to properly remove all remaining residue. Pressure wash for best results. Remove excess water with a non-metal squeegee or mop. NOTE: Heavily stained areas or older stains may require an additional application. The

surface is ready when it feels like medium grit sandpaper and no residue or loose concrete remains on the surface.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Thoroughly rinse all surfaces, clothing and tools with fresh water after use.
For disposal of unused paint products, please contact your household refuse collection service.
If product comes in contact with painted or finished surfaces, rinse immediately with fresh water.

† WARNING! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES	MPI #	25

SURFACE PREPARATION:

New concrete must cure for a minimum of 30 days. Wipe up all excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on the surface. Completely strip all existing coatings using BEHR® Concrete & Masonry Paint Stripper No. 992 prior to use. Be sure to rinse thoroughly before treating with BEHR® Concrete & Masonry Cleaner & Etcher No. 991. Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Prevent all rinse solution from entering storm drains.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.
DANGER! CORROSIVE! WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS ORGANIC SALT. AVOID CONTACT WITH SKIN. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





CONCRETE & MASONRY PAINT STRIPPER NO. 992 BIODEGRADABLE & EASY WATER CLEAN-UP



PRODUCT INFORMATION

BEHR® CONCRETE & MASONRY PAINT STRIPPER is part of the BEHR family of Concrete & Masonry Prep products. It is a biodegradable stripper that removes multiple layers of coatings on vertical and horizontal surfaces. It is formulated to strip stains, epoxies, urethanes, elastomers, alkyds, sealants and most industrial and architectural coatings. BEHR CONCRETE & MASONRY PAINT STRIPPER NO. 992 is designed for Interior & Exterior Metal, Masonry, Stone, Brick and Concrete Surfaces such as: Garage Floors, Driveways, Walkways, Patios, Basement Floors and Concrete Walls.

RECOMMENDED USES:

Use on painted or stained Interior/Exterior Concrete, Masonry, Stone, Brick and Metal Surfaces such as: Garage Floors, Driveways, Walkways, Patios, Basement Floors and Concrete Walls. Removes coatings such as: stains, epoxies, urethanes, elastomeric, alkyds, sealants, latex and most industrial and architectural paints. **DO NOT USE ON MARBLE, GRANITE, TERRAZZO, COLORED CONCRETE, BRASS, BRONZE or COPPER.** CAUTION: Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

PRODUCT SPECIFICATIONS:

- No. 992 128 oz
- Active: Glycolic Acid
- *Weight per Gallon: 8.5 +/- 0.2 lbs./gal
- *% Solids:
 - By Weight: 8.9 +/- 2%
- VOC (C.O.V.): 40.6 wt %
- Flash Point: Not Applicable
- Viscosity: 95-100 KU

APPLICATION:

Use product when air and surface temperatures are between 50-90°F (10°-32°C). Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge. Apply a thick, even layer of stripper onto the surface using a paintbrush or an airless sprayer. Stripper thickness should be such that the original coated surface is completely covered. Spread rate is approximately 60-75 sq. ft. per gallon. Penetration varies according to coating type, thickness and temperature. **COATING WILL WRINKLE WHEN THE JOB IS DONE.** Most coatings will take between 1 – 6 hours to lift. Check periodically during the waiting period, to ensure that the coating is completely covered with the stripper. If the coated surface becomes visible again, re-apply a light coating. The stripper should remain wet and active until the coating wrinkles. If hot or windy conditions cause drying, re-apply a light coating. Use a scraper, squeegee or pressure washer to remove all coating and residue. The stripper is formulated to remove several layers of coating in one application. Some areas however, may require an additional application to remove all layers. The stripped surface must be rinsed with water thoroughly to remove all chemical residues before recoating.

DRY TIME:

Surface dry time will vary, depending on air & surface temperature. Make sure concrete or surface is visually and completely dry to touch prior to recoating.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

If product comes in contact with painted or finished surfaces rinse immediately with fresh water. Thoroughly rinse all surfaces, clothing and tools with fresh water after use. Collect lifted coating and dispose of in accordance with local government regulations. For disposal of unused paint products, please contact your household refuse collection service.

† WARNING! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES		

SURFACE PREPARATION:

SHAKE WELL PRIOR TO USE. Pour the BEHR® CONCRETE & MASONRY PAINT STRIPPER NO.992 into a paint tray or bucket. If water seems to have separated out, stir product until uniform. For vertical and glossy or greasy surfaces, scuff sand the surface lightly with a medium grit sand paper prior to application to prevent sagging of paint stripper. Test Patch: A test area will indicate the time required to lift coating and the suitability of the product for the paint and substrate. Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Prevent all rinse solution from entering storm drains.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **CAUTION! IRRITANT! MAY CAUSE MODERATE EYE IRRITATION. HARMFUL IF SWALLOWED. CONTAINS GLYCOLIC ACID. AVOID CONTACT WITH SKIN. MAY CAUSE SLIGHT SKIN IRRITATION AND MODERATE TO SEVERE GASTROINTESTINAL AND RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION.** Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, **DO NOT** induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.

