



**ELASTOMERIC MASONRY, STUCCO & BRICK PAINT**

NO. 68 ULTRA PURE WHITE®



**PRODUCT INFORMATION**

BEHR® ELASTOMERIC MASONRY, STUCCO & BRICK PAINT is a flexible, high-build coating designed to expand and contract, bridging hairline cracks in exterior, vertical masonry surfaces. This waterproofing paint is extremely durable and is mildew and dirt resistant. It has superior elasticity and elongation properties, stretching up to 600%. It passes Federal Specification TT-C-555b sec. 3.3.3, withstanding 98-mph wind-driven rain. This 100% acrylic latex formula provides a breathable film, releasing moisture that builds in walls. This low-sheen paint has excellent color retention and is available in 63 custom tinted colors.

**RECOMMENDED USES:**

Use on properly prepared and primed, vertical surfaces including stucco, masonry, concrete, concrete block or brick as well as adjacent wood and metal surfaces.

**PRODUCT SPECIFICATIONS:**

**Tint Bases/Max Tint Load:**

\*No. 68 Ultra Pure White® 124 oz / 6 oz

**Sheen:** 3.5-5.5 @ 85°

**Vehicle Type:** Acrylic Latex

**\*Weight per Gallon:** 10.8 +/- 0.2 lbs./gal

**\*% Solids:**

By Volume: 48.0 +/- 2%

By Weight: 59.6 +/- 2%

**VOC:** <50 g/l

**Flash Point:** Not Applicable

**Viscosity:** 120-130 KU

**Elongation:** 600%

**Wind Driven Rain:**

98 mph ASTM TT-C-555B

**Perm Rating:** 9 US Perms

**\*Recommended Film Thickness:**

Wet: 21.3 mils / Dry: 10.2 mils @ 75 SFPG

Wet: 12.8 mils / Dry: 6.1 mils @ 125 SFPG

**\*Coverage:** 75-125 Square Feet Per Gallon depending on application method and substrate porosity. Does not include the loss of material from spraying.

**APPLICATION:**

**Brush:** Nylon/polyester

**Roller:** Use 1 1/4" nap cover.

**Air-less Spray:** At packaged consistency

**Tip:** .025"-.029"

**Filter:** 60 mesh

**Thinning:** (If required) No more than 1/2 pint of water per gallon.

† **Dry Time:** @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

† To Touch: 4-6 hours

† To Recoat: 24 hours

† Full Cure: 2 weeks

**RECOMMENDED PRIMER/SYSTEMS:**

**Masonry:**

• BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

**Masonry with pH Levels up to 13.0:**

- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436
- BEHR® Interior/Exterior Basement & Masonry Waterproof No. 875 or BEHR® Interior/Exterior Concrete & Masonry Waterproof No. 870

**Wood:**

- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436
- BEHR PREMIUM PLUS® Interior/Exterior Oil-Based Primer & Sealer No. 434 on properly prepared surfaces.

**Galvanized Metal, Metal & Aluminum:**

- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

**NEW SURFACES:**

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

**PREVIOUSLY PAINTED SURFACES:**

- Use a full coat or spot prime with BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436, or use BEHR PREMIUM PLUS® Interior/Exterior Oil-Based Primer & Sealer No. 434 on properly prepared surfaces.

COMPLIES WITH THE BELOW AS OF 3/22/2011			
OTC	YES	CARB	YES
SCAQMD	YES	MPI #	113

**CAUTIONS/LIMITATIONS:**

- Protect from freezing.
- Do not use on floors.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Allow two weeks for full cure before washing or cleaning.
- Shelf life under normal conditions is two years unopened.

**CLEAN UP:**

Clean all tools and equipment with soap and water. To recycle or dispose of paint, contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN.**

**PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





## ELASTOMERIC MASONRY, STUCCO &amp; BRICK PAINT

## NO. 68 ULTRA PURE WHITE®

**SURFACE PREPARATION:**

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust, and all other foreign substances.

**Mildew Stains:** Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m<sup>2</sup>). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength. **New Wood:** Follow up mildew stain removal with BEHR® Premium 2-in-1 Wood Prep No. 63 after application to remove mill glaze to condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions.

**New Wood:** Remove mill glaze with sandpaper. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating. **Previously Painted Wood:** Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a tack or wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

**Glossy Surfaces:** For maximum adhesion, sand the surface thoroughly before coating.

**Wood:** WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**Stain-blocking:** After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before top-coating the entire area. If bleeding continues, a longer dry time of the primer may be needed before top-coating.

**Masonry:** All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using BEHR® Concrete & Masonry Cleaner & Etcher No. 991 or with mechanical means. Use BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 to remove loose aggregate and debris. Scrub vigorously into the surface with a plastic brush, broom, or power washer. Rinse thoroughly with water and allow drying.

**Galvanized Metal, Metal & Aluminum:** The oil film on new galvanized metal must be removed before it is painted. Remove oil film with a detergent and water solution. For better paint adhesion, sand the surface with sandpaper, steel wool, or by using BEHR® Concrete & Masonry Cleaner & Etcher No. 991. Clean by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Metal: Remove all rust and mill scale using sandpaper, steel wool, abrasive blasting, or other abrading methods to create a profile on the metal's surface. **New Surfaces:** Clean the metal by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be primed the same day it is cleaned.

**GENERAL INFORMATION:**

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**





## CONCRETE & MASONRY WATERPROOFER

### NO. 870



### PRODUCT INFORMATION

BEHR® CONCRETE & MASONRY WATERPROOFER with NanoGuard® technology, is a premium, interior/exterior waterproofing paint designed for porous concrete and masonry surfaces. This low odor, masonry paint is formulated for waterproofing above and below grade basement walls, masonry walls, retaining walls, cinder & concrete blocks, stucco and brick. This alkali resistant coating provides a long-lasting, durable and decorative finish that resists water seeping under hydrostatic pressure. It uses NanoGuard® technology to form an extremely strong adhesive barrier to stop water infiltration.

### RECOMMENDED USES:

Use on above or below grade basement walls, retaining walls, masonry walls, cinder blocks, stucco, brick, and cut masonry units. Not for use on floors or walls with active water leaks. Do not use over oil- or latex-based paint.

### PRODUCT SPECIFICATIONS:

#### Tint Bases/Max Tint Load:

- \*No. 870 White 124 oz / 6 oz
- No. 2-870 White 124 oz / 6 oz

**Gloss:** <5 @ 60°

**Sheen:** <4 @ 85°

**Vehicle Type:** 100% Styrene Acrylic Latex

**\*Weight per Gallon:** 11.7 +/- 0.2 lbs./gal

#### \*% Solids:

- By Volume: 44.5 +/- 2%
- By Weight: 60.1 +/- 2%

**VOC:** No. 870 <250 g/l

**Low VOC:** No. 2-870 <100 g/l

**Flash Point:** Not Applicable

**Viscosity:** 100-110 KU

#### \*Recommended Film Thickness:

- Wet: 21.3 Dry: 9.5 mils @ 75 SFPG
- Wet: 12.8 Dry: 5.7 mils @ 125 SFPG

**\*Coverage:** 75-125 Square Feet Per Gallon, depending on application method and substrate porosity. Does not include the loss of material from spraying.

### APPLICATION:

**Brush:** Nylon/polyester blend

**Roller:** See label instruction.

**Air-less Spray:** Fluid pressure, 2,200-3,200 PSI.

**Tip:** .023" - .025"

**Filter:** Remove

**Thinning:** Not recommended. Product is formulated for use at package consistency only.

**† Dry Time:** @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

- † To Touch: 1 hour
- † To Recoat: 4 hours
- † Full Cure: 7-14 days

### RECOMMENDED PRIMER / SYSTEMS:

#### Masonry: Stucco, Cinder Block, Cut Masonry Units (CMUs), Split Face Block

- BEHR® Concrete & Masonry Protector & Waterproofer No. 980 (Do not use on smooth or nonporous concrete.)
- BEHR® Concrete & Masonry Bonding Primer No. 880
- BEHR® Interior/Exterior Basement & Masonry Waterproofer No. 875, or BEHR® Interior/Exterior Concrete & Masonry Waterproofer No. 870 (can also be used as a block filler.)
- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

#### Masonry: Cement Composition Panels/ Siding, Exterior Insulation and Finish Systems (EIFS) or Synthetic Stucco

- BEHR® Concrete & Masonry Bonding Primer No. 880
- BEHR® Interior/Exterior Basement & Masonry Waterproofer No. 875, or BEHR® Interior/Exterior Concrete & Masonry Waterproofer No. 870 (can also be used as a block filler.)
- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

#### Masonry with pH Levels up to 13.0:

- BEHR® Interior/Exterior Basement & Masonry Waterproofer No. 875, or BEHR® Interior/Exterior Concrete & Masonry Waterproofer No. 870
- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

#### Galvanized Metal, Metal & Aluminum:

- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

#### New Surfaces:

- All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow drying.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES		

#### Previously Painted Surfaces:

- Use a full coat or spot prime with BEHR® Interior/Exterior Concrete & Masonry Waterproofer No. 870 on properly prepared surfaces.

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use when air and surface temperatures are below 35°F and above 90°F.
- Avoid heavy traffic for 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened

### CLEAN UP:

Clean all tools and equipment with soap and water. To recycle or dispose of paint, contact your household refuse collection service.

**† WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





## CONCRETE &amp; MASONRY WATERPROOFING PAINT

NO. 870

**SURFACE PREPARATION:**

All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow drying.

**Mildew Stains:** All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m<sup>2</sup>). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength. **New Wood:** Follow up mildew stain removal with BEHR® Premium 2-in-1 Wood Prep No. 63 after application to remove mill glaze to condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions. **Interior:** Use one part BEHR® Premium Mold & Mildew Stain Remover No. 62 to three parts water (1:3 dilution). **DO NOT USE FULL STRENGTH.** Avoid contact with clothing, carpet and fabrics. Apply using a clean cloth or sponge. Thoroughly rinse the surface with fresh water. Prolonged exposure on painted surfaces may damage finish.

**Masonry: Stucco, Concrete, Cut Masonry Units (CMUs), Split-Faced Block: New:** All masonry surfaces must be cured at least 7 days before painting. The pH must be 13.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using BEHR® Concrete & Masonry Cleaner & Etcher No. 991 or with mechanical means. Use BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 to remove loose aggregate and debris. Scrub vigorously into the surface with a plastic brush broom or power washer. Rinse thoroughly with water and allow drying.

**Masonry: Cement Composition Panels/Siding, Exterior Insulation and Finish Systems (EIFS) or Synthetic Stucco:**

**New:** All masonry surfaces must be cured at least 7 days before painting. The pH must be 13.0 or lower prior to coating. All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the substrate. **Previously Painted Surface:** All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow drying.

**GENERAL INFORMATION:**

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. FOR TINT BASES - DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.**

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING IN VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing; leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**





## BASEMENT & MASONRY WATERPROOFER

NO. 875



### PRODUCT INFORMATION

BEHR® BASEMENT & MASONRY WATERPROOFING PAINT with NanoGuard® technology, is a premium, interior/exterior waterproofing paint designed for porous concrete and masonry surfaces. This low odor, masonry paint is formulated for waterproofing above and below grade basement walls, masonry walls, retaining walls, cinder & concrete blocks, stucco and brick. This alkali resistant coating provides a long-lasting, durable and decorative finish that resists water seeping under hydrostatic pressure. It uses NanoGuard® technology to form an extremely strong adhesive barrier to stop water infiltration.

### RECOMMENDED USES:

Use on above or below grade basement walls, retaining walls, masonry walls, cinder blocks, stucco, brick, and cut masonry units. Not for use on walls with active water leaks. Do not use over oil- or latex-based paint.

### PRODUCT SPECIFICATIONS:

**Tint Bases/Max Tint Load:**

- \*No. 875 White 124 oz / 6 oz
- No. 2-875 White 124 oz / 6 oz

**Gloss:** 0-5 @ 60°

**Sheen:** 0-4 @ 85°

**Vehicle Type:** 100% Styrene Acrylic Latex

**\*Weight per Gallon:** 11.7 +/- 0.2 lbs./gal

**\*% Solids:**

- By Volume: 44.5 +/- 2%
- By Weight: 60.1 +/- 2%

**VOC:** No. 875 <250 g/l

**Low VOC:** No. 2-875 <100 g/l

**Flash Point:** Not Applicable

**Viscosity:** 100-110 KU

**\*Recommended Film Thickness:**

- Wet: 21.3 Dry: 9.5 mils @ 75 SFPG
- Wet: 12.8 Dry: 5.7 mils @ 125 SFPG

**\*Coverage:** 75-125 Square Feet Per Gallon, depending on application method and substrate porosity. Does not include the loss of material from spraying.

### APPLICATION:

**Brush:** Nylon/polyester blend

**Roller:** See label instruction.

**Air-less Spray:** Fluid pressure, 2,200-3,200psi.

**Tip:** .023" - .025"

**Filter:** Remove

**Thinning:** Not recommended. Product is formulated for use at package consistency only.

† **Dry Time:** @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

- † To Touch: 1 hour
- † To Recoat: 4 hours
- † Full Cure: 7-14 days

### RECOMMENDED PRIMER/SYSTEMS:

**Masonry: Stucco, Cinder Block, Cut Masonry Units (CMUs), Split Face Block**

- BEHR® Concrete & Masonry Protector & Waterproofing No. 980 (Do not use on smooth or nonporous concrete.)
- BEHR® Concrete & Masonry Bonding Primer No. 880
- BEHR® Interior/Exterior Basement & Masonry Waterproofing No. 875, or BEHR® Interior/Exterior Concrete & Masonry Waterproofing No. 870 (can also be used as a block filler.)
- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

**Masonry: Cement Composition Panels/Siding, Exterior Insulation and Finish Systems (EIFS) or Synthetic Stucco**

- BEHR® Concrete & Masonry Bonding Primer No. 880
- BEHR® Interior/Exterior Basement & Masonry Waterproofing No. 875, or BEHR® Interior/Exterior Concrete & Masonry Waterproofing No. 870 (can also be used as a block filler.)
- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

**Masonry with pH Levels up to 13.0:**

- BEHR® Interior/Exterior Basement & Masonry Waterproofing No. 875, or BEHR® Interior/Exterior Concrete & Masonry Waterproofing No. 870
- BEHR PREMIUM PLUS® Exterior Water-Based Primer & Sealer No. 436

**NEW SURFACES:**

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

**PREVIOUSLY PAINTED SURFACES:**

- Use a full coat or spot prime with BEHR® BASEMENT & MASONRY WATERPROOFING PAINT No. 875 on properly prepared surfaces.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES		

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use when air and surface temperatures are below 35°F and above 90°F.
- Avoid heavy traffic for 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened

### CLEAN UP:

Clean all tools and equipment with soap and water. To recycle or dispose of paint, contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





## BASEMENT &amp; MASONRY WATERPROOFER

NO. 875

**SURFACE PREPARATION:**

All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow drying.

**Mildew Stains:** All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m<sup>2</sup>). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength. **New Wood:** Follow up mildew stain removal with BEHR® Premium 2-in-1 Wood Prep No. 63 after application to remove mill glaze to condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions. **Interior:** Use one part BEHR® Premium Mold & Mildew Stain Remover No. 62 to three parts water (1:3 dilution). DO NOT USE FULL STRENGTH. Avoid contact with clothing, carpet and fabrics. Apply using a clean cloth or sponge. Thoroughly rinse the surface with fresh water. Prolonged exposure on painted surfaces may damage finish.

**Tannin Bleed & Stainblocking:** After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before top-coating the entire area. If bleeding continues, a longer dry time of the primer may be needed before top-coating or an additional coat of primer may be required to block the tannin bleed or stain.

**Masonry: Stucco, Concrete, Cut Masonry Unit's (CMUs), Split-Faced Block:** New: All masonry surfaces must be cured at least 7 days before painting. The pH must be 13.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using BEHR® Concrete & Masonry Cleaner & Etcher No. 991 or with mechanical means. Use BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 to remove loose aggregate and debris. Scrub vigorously into the surface with a plastic brush broom or power washer. Rinse thoroughly with water and allow drying.

**Masonry: Cement Composition Panels/Siding, Exterior Insulation and Finish Systems (EIFS) or Synthetic Stucco:** New: All masonry surfaces must be cured at least 7 days before painting. The pH must be 13.0 or lower prior to coating. All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the substrate. Previously Painted Surface: All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow drying:

**GENERAL INFORMATION:**

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. FOR TINT BASES - DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.**

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING IN VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing; leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**





## CONCRETE & MASONRY PROTECTOR & WATERPROOFER

### NO. 980



### PRODUCT INFORMATION

BEHR® CONCRETE & MASONRY PROTECTOR & WATERPROOFER is a premium, interior/exterior, waterproofing formula that uses the latest water-based, silicone technology designed to penetrate surfaces up to 1/2". This waterproofer creates a barrier inside the surface that keeps water out, but lets trapped water vapors escape; reducing corrosion, spalling, efflorescence and freeze-thaw damage. It reduces staining due to mold and mildew, and ensures greater durability of the surface. The protection is not worn away with normal use. It protects long after the water beading is gone.

### RECOMMENDED USES:

Use on horizontal and vertical, uncoated concrete and masonry surfaces, such as: concrete block, pavers, stucco, brick, unglazed tiles, exposed aggregate concrete, sandstone and slate. Not recommended for use on areas subject to hydrostatic pressure such as basement walls or floors.

### PRODUCT SPECIFICATIONS:

**Vehicle Type:** Silicone

**\*Weight per Gallon:** 8.3 +/- 0.2 lbs./gal

**\*% Solids:**

By Volume: 7.5 +/- 2%

By Weight: 7.1 +/- 2%

**VOC:** <120 g/l (including water)

**Flash Point:** Not Applicable

**Viscosity:** 25-35 sec (#1 Zahn cup)

**\*Coverage Approximately:** 250 Square Feet Per Gallon, depending on application method and substrate porosity.

Does not include the loss of material from spraying.

### APPLICATION:

**Brush:** Nylon/polyester

**Roller:** Use 3/8"-1/2" nap cover on smooth surfaces and 1/2"-3/4" on rough, porous surfaces.

**Air-less Spray:** At packaged consistency.

**Tip:** .015"-.019"

**Filter:** 60 mesh

**Thinning:** (If required) No more than 1/2 pint of water per gallon.

**† Dry Time:** @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

† To Touch:

† To Recoat: 2-4 hours

† Full Cure: 2 weeks

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on coated or previously sealed floors.
- Do not use when air and surface temperatures are below 50°F and above 90°F.
- Avoid heavy traffic for 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.
- Masonry with pH Levels up to 13.0.

### CLEAN UP:

Clean all tools and equipment with soap and water. To recycle or dispose of paint, contact your household refuse collection service.

**† WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN.**

**PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES	MPI #	117

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





# CONCRETE & MASONRY PROTECTOR & WATERPROOFER

## NO. 980

### SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust, and all other foreign substances.

**Mildew Stains:** All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m<sup>2</sup>). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength. Follow all label instructions. **Interior:** Use one-part BEHR® Premium Mold & Mildew Stain Remover No. 62 to three parts water (1:3 dilution). **DO NOT USE FULL STRENGTH.** Avoid contact with clothing, carpet and fabrics. Apply using a clean cloth or sponge. Thoroughly rinse the surface with fresh water. Prolonged exposure on painted surfaces may damage finish.

### Masonry: Stucco, Concrete, Cut Masonry Units (CMUs), Split-Faced Block:

**New:** All masonry surfaces must be cured at least 28 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using BEHR® Concrete & Masonry Cleaner & Etcher No. 991 or with mechanical means. Use BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 to remove loose aggregate and debris. Scrub vigorously into the surface with a plastic brush broom or power washer. Rinse thoroughly with water and allow drying.

### Masonry: Cement Composition Panels/Siding, Exterior Insulation and Finish Systems (EIFS) or Synthetic Stucco:

**New:** All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the substrate. **Previously Painted Surface:** All surfaces must be clean, free of dust, chalk, mold and mildew stains, loose and peeling paint and all other foreign substances. Clean surfaces with a detergent and water solution by scrubbing the surface vigorously and rinse with a garden hose or a power washer and allow drying.

### GENERAL INFORMATION:

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**





WET-LOOK SEALER

NO. 985 HIGH GLOSS & NO. 986 LOW LUSTRE



PRODUCT INFORMATION

BEHR® WET-LOOK SEALER's are a clear, non-yellowing, high solids, acrylic-based masonry sealer. It is formulated to seal, protect and beautify concrete and masonry surfaces with a high gloss, wet-look finish. BEHR WET-LOOK SEALER NO. 985 is also an excellent topcoat for paints and stains.

RECOMMENDED USES:

Use on Previously Coated or Uncoated, Vertical or Horizontal, Interior or Exterior surfaces such as: pavers, concrete, mexican tile and unglazed tiles, brick, aggregate, natural and artificial stone, masonry and stucco. Not recommended for use on wood, metal, granite, marble, terrazzo, areas immediately adjacent to pools or areas subject to hydrostatic pressure. Do not use over oil-based products. CAUTION: Sealed surfaces may become slippery when wet. Use caution when walking on surface when moisture is present. Apply in sections so wet material does not have to be walked on during application.

PRODUCT SPECIFICATIONS:

Bases:

- \*No. 985 Wet Look High Gloss 128 oz
- No. 986 Wet Look Low Lustre 128 oz

Vehicle Type: Acrylic

\*Weight per Gallon: 8.5 +/- 0.2 lbs./gal

\*% Solids:

- By Volume: 30.5 +/- 2%
- By Weight: 32.9 +/- 2%

VOC: <100 g/l

Flash Point: Not Applicable

Viscosity: 20-35 sec, #2 Zahn Cup

\*Recommended Film Thickness:

- Wet: 8.0 Dry: 2.4 mils @ 200 SFPG
- Wet: 2.3 Dry: 0.7 mils @ 700 SFPG

\*Coverage: 200-700 Square Feet Per Gallon, depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

DO NOT THIN. Stir or shake before applying. Use product when temperature is between 50-80°F (10-27°C). Do not apply in direct sunlight. Do not apply to wet surfaces or if rain or heavy dew is expected within 24 hours. Apply a thin coat using a nylon/polyester brush, 3/8-1/2" nap roller or a high quality pump sprayer with an adjustable tip at a spread rate of 150-300 sq. ft. (14-28 m<sup>2</sup>) per gallon. Spread rate is highly dependent on surface roughness and porosity. If sprayed, backroll for uniform thickness. Allow first coat to dry 4 hours, then apply a second coat at a spread rate of 300-400 sq. ft. (28-37 m<sup>2</sup>) per gallon. Additional coats (no more than 4) may be added for a higher gloss and added protection. Note: Horizontal surfaces may be subject to excessive wear. Therefore, periodic touch-ups may be necessary.

APPLICATION TOOLS:

- Brush: Nylon/polyester
- Roller: Use 3/8"-1/2" nap cover on smooth surfaces and 1/2"-3/4" on rough, porous surfaces.
- Air-less Spray: At packaged consistency.
- Tip: .015"
- Filter: 60 mesh
- Thinning: DO NOT THIN
- Dry Time: @ 77° & 50% RH
  - Dries to the touch in 1 hour.
  - 4 hours before recoating.
  - Allow surface to dry 24-48 hours before subjecting surface to heavy foot traffic.

COMPLIES WITH THE BELOW AS OF 3/22/2011			
OTC	YES	CARB	YES
SCAQMD	YES	MPI #	99

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use when air and surface temperatures are below 50°F and above 90°F.
- Avoid heavy traffic for 24-48 hours.
- Allow 72 hours before repositioning furniture
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Brushes and other equipment can be cleaned with warm, soapy water. For disposal of empty containers and unused product, contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





## WET-LOOK SEALER

NO. 985 HIGH GLOSS & NO. 986 LOW LUSTRE

### SURFACE PREPARATION:

**Mildew Stains:** All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mold & Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m<sup>2</sup>). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength.

**Masonry: Concrete, Cut Masonry Units (CMUs), Split-Faced Block: New and Uncoated:** All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using BEHR® Concrete & Masonry Cleaner & Etcher No. 991 or with mechanical means. Remove loose aggregate and debris using BEHR® Concrete & Masonry Degreaser & Cleaner No. 990. Scrub vigorously into the surface with a plastic brush broom or power washer. Rinse thoroughly with water and allow to dry.

### GENERAL INFORMATION:

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING: IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.**

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**