


3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



**BEHR® FLAKES
FLOOR FINISH
ADDITIVE GRAY
NO. F-50**

RECOMMENDED USES:

Transform your concrete floor into a beautiful surface that has the look of granite or terrazzo. BEHR® color flakes are available in a variety of color combinations to match any décor, adding beauty and elegance to residential and commercial floors. Turn that boring concrete floor into a work of art.

AVAILABLE IN: 1 lb. bag

<u>COLORS</u>	<u>COMPOSITION</u>	<u>APPLICATION TOOLS</u>
No. F-50 Gray	Vehicle/Active Ingredient: N/A	Airless Spray: N/A
<u>Tintable Bases/Max Tint</u> N/A	Percent Solids By Volume: N/A	Conventional Spray: N/A
<u>FINISH</u> None	Percent Solids By Weight: N/A	Brush: N/A
<u>COVERAGE RATE</u> 200-250 sq. ft. per 1lb bag	Weight Per Gallon: 1 lb bag	Roller: N/A.
<u>DRYING TIME</u> As per coating manufacturers instructions.	<u>VOC</u> N/A	Thinner: N/A
<u>PRIMERS</u> N/A	<u>Flashpoint</u> N/A	
	<u>MSDS</u> Available @ www.behr.com Or 1-800-854-0133 Ext. 2	<u>APPLICATION</u>
	<u>Clean Up</u> As per coating manufacturers instructions. Recycle or dispose of paint call 1-800-CLEANUP (U.S.A. only) www.earth911.org	IMPORTANT: Toss flakes evenly over a 250 sq. ft. area. Work in 1 x 1 m (3' x 3') sections to ensure that the color flakes are evenly distributed. Apply color flakes directly onto the wet painted surface. Throw the color flakes up into the air and let them distribute evenly on the wet painted surface. Repeat these steps until you have finished the entire garage floor.
		This product, if added according to label directions, helps to prevent slipping by providing a slip-resistant coating. However, Behr does not warrant that this product will prevent accidents as described in the limited warranty below.

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2

3400 W. Segerstrom Avenue, Santa Ana, California 92704 or www.behr.com



**BEHR® FLAKES
FLOOR FINISH
ADDITIVE TAN
NO. F-55**

RECOMMENDED USES:

Transform your concrete floor into a beautiful surface that has the look of granite or terrazzo. BEHR® color flakes are available in a variety of color combinations to match any décor, adding beauty and elegance to residential and commercial floors. Turn that boring concrete floor into a work of art.

AVAILABLE IN: 1 lb Bag

COLORS

No. F-55Tan

Tintable Bases/Max Tint

N/A

FINISH

None

COVERAGE RATE

200-25- sq. ft. per 1 lb bag

DRYING TIME

As per coating manufacturers instructions.

PRIMERS

N/A

COMPOSITION

Vehicle/Active Ingredient:

N/A

Percent Solids By Volume:

N/A

Percent Solids By Weight:

N/A

Weight Per Gallon:

1 lb Bag

VOC

N/A

Flashpoint

N/A

MSDS

Available @ www.behr.com
Or 1-800-854-0133 Ext. 2

Clean Up

As per coating manufacturers instructions. Recycle or dispose of paint call 1-800-CLEANUP (U.S.A. only) www.earth911.org

APPLICATION TOOLS

Airless Spray: N/A

Conventional Spray: N/A

Brush: N/A

Roller: N/A.

Thinner: N/A

APPLICATION

IMPORTANT: Toss flakes evenly over a 250 sq. ft. area. Work in 1 x 1 m (3' x 3') sections to ensure that the color flakes are evenly distributed. Apply color flakes directly onto the wet painted surface. Throw the color flakes up into the air and let them distribute evenly on the wet painted surface. Repeat these steps until you have finished the entire garage floor.

This product, if added according to label directions, helps to prevent slipping by providing a slip-resistant coating. However, Behr does not warrant that this product will prevent accidents as described in the limited warranty below.

This information is believed to be reliable; however Behr Process Corporation makes no warranty, guarantee, or representation and assumes no liability as to the absolute correctness or sufficiency of the specifications.

To Consult with a Technical Service Representative call 1-800-854-0133 Ext. 2