



## DECORATIVE COLOR FLAKES

NO. F-50 GRAY, F-55 TAN & F-60 METALLIC



### PRODUCT INFORMATION

Transform your concrete floor into a beautiful surface that has the look of granite or terrazzo. BEHR® Color Flakes are available in a variety of color combinations to match any décor, adding beauty and elegance to residential and commercial floors. Turn that boring concrete floor into a work of art.

### RECOMMENDED USES:

Use on Interior/Exterior surfaces such as: garage floors, driveways, basements, patios, sidewalks, laundry rooms and pool/cool decks. BEHR Color Flakes help to hide dirt and surface imperfections and can be used with water and oil-based coatings.

### PRODUCT SPECIFICATIONS:

#### Tint Bases/Max Tint Load:

N/A

#### Pre-Mixed Colors:

NO. F-50 Gray

NO. F-55 Tan

NO. F-60 Metallic

#### Vehicle Type: N/A

\*Weight per Gallon: 1 lb bag

\*% Solids: N/A

VOC: N/A

Flash Point: N/A

\*Coverage: 200-250 SFPG, depending on application method.

### APPLICATION:

**Important:** Toss flakes evenly over a 250 sq. ft. area. Work in 1 x 1 m (3' x 3') sections to ensure that the color flakes are evenly distributed. Apply color flakes directly onto the wet painted surface. Throw the color flakes up into the air and let them distribute evenly on the wet painted surface. Repeat these steps until you have finished the entire garage floor.

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on floors.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

### CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

**† WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

### SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

**Mildew:** All surfaces must be clean of mold and mildew stains and dirt prior to coating.

**Masonry:** All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth trowel concrete, create a profile using BEHR® Concrete & Masonry Cleaner & Etcher No. 991 or with mechanical means. Remove loose aggregate and debris using BEHR® Concrete & Masonry Degreaser & Cleaner No. 990. Scrub vigorously into the surface with a plastic brush, broom or power washer. Rinse thoroughly with water and allow to dry.

### GENERAL INFORMATION:

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED.**

**CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING IN VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.**

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.

