



PREMIUM DECK, FENCE & SIDING MOLD & MILDEW STAIN REMOVER

NO. 62

PRODUCT INFORMATION

An interior/exterior cleaner formulated to remove stains caused by mold, mildew, algae and fungus. It cleans dirt and stains while lightening old, weathered wood. Removes mildew stains quickly and easily. This product is ready-to-use with no mixing required and is easy to clean up... just use water.

RECOMMENDED USES:

INTERIOR: Use on, Interior Mildew-Stained Surfaces, Bathroom and Kitchen areas, and Woodwork. **EXTERIOR:** Use on stains caused by mold, mildew, algae & fungus. Does not contain bleach and will not damage wood surfaces. Use full strength on: Exterior Mildew-Stained Surfaces of all types including Wood, Concrete, Masonry, Stucco, Stone, Brick, Vinyl and Aluminum Siding, Composite, Tile, Plastic, Fiberglass and Roofing materials. Use BEHR® PREMIUM 2-IN-1 WOOD PREP NO. 63 after application to remove mill glaze, condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions.

PRODUCT SPECIFICATIONS:

No. 62 128 oz

***Weight per Gallon:** 8.4 +/- 0.2 lbs./gal

***% Solids:** By Weight: Not Applicable

VOC: 0 (g/l)

Flash Point: Not Applicable

Viscosity: Water thin

SURFACE PREPARATION:

To remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood decks, siding, fences, shakes and shingles use BEHR® PREMIUM STAIN & FINISH STRIPPER NO. 64.

Use BEHR PREMIUM 2-IN-1 WOOD PREP NO. 63 to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae & fungus. Rinse thoroughly. Allow to dry. Apply coating. On new wood use NO. 63 to remove mill glaze and open the pores of the wood. For severe stains caused by mold, mildew, algae & fungus apply BEHR PREMIUM MOLD & MILDEW STAIN REMOVER NO. 62 and rinse prior to applying BEHR PREMIUM 2-IN-1 WOOD PREP NO. 63.

APPLICATION:

EXTERIOR: Use product at full strength. Apply using a pump sprayer, brush, mop, or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of product will treat 200-250 sq. ft. (19-23 m²). Allow product to work for at least one minute to remove mildew stains. Do not allow product to dry on surface. Rinse surface and surrounding area thoroughly with water from garden hose using nozzle at normal pressure, or use pressure washer at low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm wood. Prolonged exposure on painted surfaces may damage finish.

INTERIOR: Product must be diluted with one part BEHR® PREMIUM MOLD & MILDEW STAIN REMOVER NO. 62 to three parts water (1:3 dilution). **DO NOT USE FULL STRENGTH.**

Avoid contact with clothing, carpet and fabrics. Apply using a clean cloth or sponge. Thoroughly rinse the surface with fresh water. Prolonged exposure on painted surface may damage finish.

CLEAN UP:

Biodegradable. Rinse all equipment with water before storage or reuse. Clean with soap & water. Properly dispose of all soiled rags and protect unused product from freezing. For disposal of unused paint products, please contact your household refuse collection service.



CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. **NOTE:** If the surface is hot to the touch it should be considered to hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- **CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

Wood: WARNING! Sanding or scraping pressure treated

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





PREMIUM DECK, FENCE & SIDING MOLD & MILDEW STAIN REMOVER

NO. 62

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

CAUTION. IRRITANT. MAY CAUSE EYE AND SKIN IRRITATION. PROLONGED INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED.

FIRST AID: In case of eye or skin contact, flush immediately with water for 20 minutes. For respiratory tract irritation, remove to fresh air.

In case of ingestion, do not induce vomiting. Drink plenty of water and get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



CONCRETE & MASONRY DEGREASER & CLEANER

NO. 990



PRODUCT INFORMATION

Extremely effective when used full strength to remove greasy, oily stains such as transmission fluid and anti-freeze caused by automobiles, motorcycles and bicycles. Use a diluted solution on lightly stained and soiled areas. Ideal for removing mildew stains, dirt and most fluids from concrete surfaces.

RECOMMENDED USES:

Use on Interior/Exterior surfaces such as: Garage Floors, Driveways, Patios, Walkways, Porches, Basement Floors and Pool Decks. Great on Concrete, Brick, Stone, Asphalt and Exposed Aggregate.

PRODUCT SPECIFICATIONS:

No. 990 128 oz

Actives: Citrus/Alkali

***Weight per Gallon:** 9.0 +/- 0.2 lbs./gal

***% Solids:**

By Weight: 17.2 +/- 2%

VOC (C.O.V.): 3.7 wt %

Flash Point: Not Applicable

Viscosity: Not Applicable

APPLICATION:

Mixing: Do not mix BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 with bleach, household or industrial cleaning products or detergents. Mix only in plastic containers.

DO NOT MIX IN A METAL CONTAINER. Use a plastic mixing container, large enough to hold up to 5 gallons of diluted solution. Use BEHR® Concrete & Masonry Degreaser & Cleaner No. 990 full strength for tough stains. For general cleaning, add 1 quart cleaner in 1 gallon of water (1:4 dilution). For cleaning previously painted surfaces, add 1 cup cleaner in 1 gallon of water (1:16 dilution). Stir diluted solution thoroughly. Avoid splashing. Wear protective clothing, goggles and acid resistant rubber gloves & boots. One gallon of diluted solution will clean and degrease up to 500 sq. ft. (47 m²) and one gallon of full strength will cover 150 sq. ft. (14 m²). Actual coverage will depend on method of application, texture and surface porosity. Wet the surface first by spraying with a garden hose. Then apply the product (full strength for tough stains, diluted for general cleaning) and work into the surface with a stiff bristled, non-metal brush or broom. For best results, use a plastic watering can or plastic pump sprayer to evenly distribute product. Allow product to stand for 10-20 minutes then scrub vigorously. NOTE: Heavily stained areas or older stains may require an additional application. After application, be sure to thoroughly saturate surrounding grass and plants with fresh water. Rinse surface thoroughly with fresh water while scrubbing at the same time to properly remove all remaining residue. Pressure wash for best results. Remove excess water with a non-metal squeegee or mop.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Thoroughly rinse all surfaces, clothing and tools with fresh water after use.

If product accidentally comes in contact with painted or finished surfaces, rinse immediately with fresh water. It will damage automobile finishes if not rinsed. For disposal of unused paint products, please contact your household refuse collection service.

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

SURFACE PREPARATION:

Wipe up all excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on surface. Test Patch: Conduct a small test patch in an inconspicuous area to ensure product performance. Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Prevent all rinse solution from entering storm drains.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

DANGER! CORROSIVE! WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS POTASSIUM HYDROXIDE. AVOID CONTACT WITH SKIN. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.



CONCRETE & MASONRY CLEANER & ETCHER NO. 991 BIODEGRADABLE & EASY WATER CLEAN-UP



PRODUCT INFORMATION

BEHR CONCRETE & MASONRY CLEANER & ETCHER is part of the BEHR family of Concrete & Masonry Prep products. It is an interior/ exterior, 2-in-1 cleaner and etcher specifically formulated to prepare the surface prior to coating. It is designed to clean and etch bare concrete and masonry surfaces to improve penetration and adhesion of paints, stains and sealers. This biodegradable and easy water clean-up product will remove grease, oil, auto fluids, rust and red clay stains from any concrete and masonry surface. BEHR NO. 991 is ideal for use on uncoated surfaces such as: garage floors, driveways, walkways, patios, basement floors and walls.

RECOMMENDED USES:

Use on Interior/Exterior uncoated surfaces such as: garage floors, driveways, walkways, patios, basement floors and concrete walls. Removes grease, oil, auto fluids, rust and red clay stains. **DO NOT USE ON MARBLE, GRANITE, TERRAZZO, COLORED CONCRETE, BRASS, BRONZE or COPPER.** NOTE: If etching is not desired, use BEHR® CONCRETE & MASONRY DEGREASER & CLEANER NO. 990.

PRODUCT SPECIFICATIONS:

- No. 991** 128 oz
- Actives:** Organic Salt
- *Weight per Gallon:** 9.1 +/- 0.2 lbs./gal
- *% Solids:**
 - By Weight: 30.6 +/- 2%
- VOC (C.O.V.):** 0 wt %
- Flash Point:** Not Applicable
- Viscosity:** Water-thin

APPLICATION:

Mixing: DO NOT MIX IN A METAL CONTAINER. Use a plastic mixing container, large enough to hold up to 2 gallons of diluted solution. Use full strength on hard to clean interior/ exterior stained surfaces and smooth concrete. Always work in a well-ventilated area. For new and lightly stained concrete or to etch galvanized metal, use a diluted solution of 1 part BEHR® Concrete & Masonry Cleaner & Etcher No. 991 to 1 part water (1:1 dilution). Stir diluted solution thoroughly. Avoid splashing. Wear protective clothing, goggles and acid resistant rubber gloves & boots. Avoid splashing. Spraying is not recommended. One gallon of full strength product will etch and clean 150-200 sq. ft. (14-18 m²). One gallon of diluted solution will etch and clean 300-400 sq. ft. (28-37 m²). Actual coverage depends on porosity and severity of surface. For best results, use a plastic watering can to evenly distribute product or spread product using a stiff bristled, non-metal brush or broom. On sloped surfaces, start at the lowest point working up to the highest point. Apply BEHR® Concrete & Masonry Cleaner & Etcher No. 991 to a dry surface for best results. Allow product to stand for 10-20 minutes then scrub vigorously. Do not let product dry on the surface. Rinse surface thoroughly with fresh water while scrubbing at the same time to properly remove all remaining residue. Pressure wash for best results. Remove excess water with a non-metal squeegee or mop. NOTE: Heavily stained areas or older stains may require an additional application. The

surface is ready when it feels like medium grit sandpaper and no residue or loose concrete remains on the surface.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered to hot to apply this coating.
- CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

CLEAN UP:

Thoroughly rinse all surfaces, clothing and tools with fresh water after use.
For disposal of unused paint products, please contact your household refuse collection service.
If product comes in contact with painted or finished surfaces, rinse immediately with fresh water.

† WARNING! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES	MPI #	25

SURFACE PREPARATION:

New concrete must cure for a minimum of 30 days. Wipe up all excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on the surface. Completely strip all existing coatings using BEHR® Concrete & Masonry Paint Stripper No. 992 prior to use. Be sure to rinse thoroughly before treating with BEHR® Concrete & Masonry Cleaner & Etcher No. 991. Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Prevent all rinse solution from entering storm drains.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.
DANGER! CORROSIVE! WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS ORGANIC SALT. AVOID CONTACT WITH SKIN. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.

