



## CONCRETE & MASONRY PAINT STRIPPER NO. 992 BIODEGRADABLE & EASY WATER CLEAN-UP



### PRODUCT INFORMATION

BEHR® CONCRETE & MASONRY PAINT STRIPPER is part of the BEHR family of Concrete & Masonry Prep products. It is a biodegradable stripper that removes multiple layers of coatings on vertical and horizontal surfaces. It is formulated to strip stains, epoxies, urethanes, elastomers, alkyds, sealants and most industrial and architectural coatings. BEHR CONCRETE & MASONRY PAINT STRIPPER NO. 992 is designed for Interior & Exterior Metal, Masonry, Stone, Brick and Concrete Surfaces such as: Garage Floors, Driveways, Walkways, Patios, Basement Floors and Concrete Walls.

### RECOMMENDED USES:

Use on painted or stained Interior/Exterior Concrete, Masonry, Stone, Brick and Metal Surfaces such as: Garage Floors, Driveways, Walkways, Patios, Basement Floors and Concrete Walls. Removes coatings such as: stains, epoxies, urethanes, elastomeric, alkyds, sealants, latex and most industrial and architectural paints. **DO NOT USE ON MARBLE, GRANITE, TERRAZZO, COLORED CONCRETE, BRASS, BRONZE or COPPER.** CAUTION: Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

### PRODUCT SPECIFICATIONS:

**No. 992** 128 oz  
**Active:** Glycolic Acid  
**\*Weight per Gallon:** 8.5 +/- 0.2 lbs./gal  
**\*% Solids:**  
 By Weight: 8.9 +/- 2%  
**VOC (C.O.V.):** 40.6 wt %  
**Flash Point:** Not Applicable  
**Viscosity:** 95-100 KU

### APPLICATION:

Use product when air and surface temperatures are between 50-90°F (10°-32°C). Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge. Apply a thick, even layer of stripper onto the surface using a paintbrush or an airless sprayer. Stripper thickness should be such that the original coated surface is completely covered. Spread rate is approximately 60-75 sq. ft. per gallon. Penetration varies according to coating type, thickness and temperature. **COATING WILL WRINKLE WHEN THE JOB IS DONE.** Most coatings will take between 1 – 6 hours to lift. Check periodically during the waiting period, to ensure that the coating is completely covered with the stripper. If the coated surface becomes visible again, re-apply a light coating. The stripper should remain wet and active until the coating wrinkles. If hot or windy conditions cause drying, re-apply a light coating. Use a scraper, squeegee or pressure washer to remove all coating and residue. The stripper is formulated to remove several layers of coating in one application. Some areas however, may require an additional application to remove all layers. The stripped surface must be rinsed with water thoroughly to remove all chemical residues before recoating.

### DRY TIME:

Surface dry time will vary, depending on air & surface temperature. Make sure concrete or surface is visually and completely dry to touch prior to recoating.

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. **NOTE:** If the surface is hot to the touch it should be considered to hot to apply this coating.
- **CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

### CLEAN UP:

If product comes in contact with painted or finished surfaces rinse immediately with fresh water. Thoroughly rinse all surfaces, clothing and tools with fresh water after use. Collect lifted coating and dispose of in accordance with local government regulations. For disposal of unused paint products, please contact your household refuse collection service.

**† WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES		

### SURFACE PREPARATION:

SHAKE WELL PRIOR TO USE. Pour the BEHR® CONCRETE & MASONRY PAINT STRIPPER NO.992 into a paint tray or bucket. If water seems to have separated out, stir product until uniform. For vertical and glossy or greasy surfaces, scuff sand the surface lightly with a medium grit sand paper prior to application to prevent sagging of paint stripper. **Test Patch:** A test area will indicate the time required to lift coating and the suitability of the product for the paint and substrate. Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Prevent all rinse solution from entering storm drains.

### GENERAL INFORMATION:

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **CAUTION! IRRITANT! MAY CAUSE MODERATE EYE IRRITATION. HARMFUL IF SWALLOWED. CONTAINS GLYCOLIC ACID. AVOID CONTACT WITH SKIN. MAY CAUSE SLIGHT SKIN IRRITATION AND MODERATE TO SEVERE GASTROINTESTINAL AND RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION.** Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, **DO NOT** induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





## CONCRETE & MASONRY PAINT STRIPPER NO. 992 BIODEGRADABLE & EASY WATER CLEAN-UP



### PRODUCT INFORMATION

BEHR® CONCRETE & MASONRY PAINT STRIPPER is part of the BEHR family of Concrete & Masonry Prep products. It is a biodegradable stripper that removes multiple layers of coatings on vertical and horizontal surfaces. It is formulated to strip stains, epoxies, urethanes, elastomers, alkyds, sealants and most industrial and architectural coatings. BEHR CONCRETE & MASONRY PAINT STRIPPER NO. 992 is designed for Interior & Exterior Metal, Masonry, Stone, Brick and Concrete Surfaces such as: Garage Floors, Driveways, Walkways, Patios, Basement Floors and Concrete Walls.

### RECOMMENDED USES:

Use on painted or stained Interior/Exterior Concrete, Masonry, Stone, Brick and Metal Surfaces such as: Garage Floors, Driveways, Walkways, Patios, Basement Floors and Concrete Walls. Removes coatings such as: stains, epoxies, urethanes, elastomeric, alkyds, sealants, latex and most industrial and architectural paints. **DO NOT USE ON MARBLE, GRANITE, TERRAZZO, COLORED CONCRETE, BRASS, BRONZE or COPPER.** CAUTION: Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

### PRODUCT SPECIFICATIONS:

**No. 992** 128 oz  
**Active:** Glycolic Acid  
**\*Weight per Gallon:** 8.5 +/- 0.2 lbs./gal  
**\*% Solids:**  
 By Weight: 8.9 +/- 2%  
**VOC (C.O.V.):** 40.6 wt %  
**Flash Point:** Not Applicable  
**Viscosity:** 95-100 KU

### APPLICATION:

Use product when air and surface temperatures are between 50-90°F (10°-32°C). Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge. Apply a thick, even layer of stripper onto the surface using a paintbrush or an airless sprayer. Stripper thickness should be such that the original coated surface is completely covered. Spread rate is approximately 60-75 sq. ft. per gallon. Penetration varies according to coating type, thickness and temperature. **COATING WILL WRINKLE WHEN THE JOB IS DONE.** Most coatings will take between 1 – 6 hours to lift. Check periodically during the waiting period, to ensure that the coating is completely covered with the stripper. If the coated surface becomes visible again, re-apply a light coating. The stripper should remain wet and active until the coating wrinkles. If hot or windy conditions cause drying, re-apply a light coating. Use a scraper, squeegee or pressure washer to remove all coating and residue. The stripper is formulated to remove several layers of coating in one application. Some areas however, may require an additional application to remove all layers. The stripped surface must be rinsed with water thoroughly to remove all chemical residues before recoating.

### DRY TIME:

Surface dry time will vary, depending on air & surface temperature. Make sure concrete or surface is visually and completely dry to touch prior to recoating.

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying to fast. Avoid painting in direct sun. **NOTE:** If the surface is hot to the touch it should be considered to hot to apply this coating.
- **CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

### CLEAN UP:

If product comes in contact with painted or finished surfaces rinse immediately with fresh water. Thoroughly rinse all surfaces, clothing and tools with fresh water after use. Collect lifted coating and dispose of in accordance with local government regulations. For disposal of unused paint products, please contact your household refuse collection service.

**† WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

COMPLIES WITH THE BELOW AS OF 3/22/2011

OTC	YES	CARB	YES
SCAQMD	YES		

### SURFACE PREPARATION:

SHAKE WELL PRIOR TO USE. Pour the BEHR® CONCRETE & MASONRY PAINT STRIPPER NO.992 into a paint tray or bucket. If water seems to have separated out, stir product until uniform. For vertical and glossy or greasy surfaces, scuff sand the surface lightly with a medium grit sand paper prior to application to prevent sagging of paint stripper. **Test Patch:** A test area will indicate the time required to lift coating and the suitability of the product for the paint and substrate. Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths. Prevent all rinse solution from entering storm drains.

### GENERAL INFORMATION:

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **CAUTION! IRRITANT! MAY CAUSE MODERATE EYE IRRITATION. HARMFUL IF SWALLOWED. CONTAINS GLYCOLIC ACID. AVOID CONTACT WITH SKIN. MAY CAUSE SLIGHT SKIN IRRITATION AND MODERATE TO SEVERE GASTROINTESTINAL AND RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION.** Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, **DO NOT** induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

\*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





## CONCRETE & MASONRY PAINT STRIPPER

### NO. 992 BIODEGRADABLE & EASY WATER CLEAN-UP

#### GENERAL INFORMATION:

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**CAUTION! IRRITANT! MAY CAUSE MODERATE EYE IRRITATION. HARMFUL IF SWALLOWED. CONTAINS GLYCOLIC ACID. AVOID CONTACT WITH SKIN. MAY CAUSE SLIGHT SKIN IRRITATION AND MODERATE TO SEVERE GASTROINTESTINAL AND RESPIRATORY SYSTEM IRRITATION.**

**USE WITH ADEQUATE VENTILATION.** Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection.

**FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hot line at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.