



**BEHR PREMIUM SELECT® INTERIOR/EXTERIOR
D.T.M. PRIMER & FINISH**

NO. K80

**MPI APPROVED PRODUCT
FOR MPI #134**



PRODUCT INFORMATION

BEHR PREMIUM SELECT® INTERIOR / EXTERIOR D.T.M. PRIMER & FINISH is a quality, interior/exterior, acrylic gloss primer and finish in one. This all-purpose "DIRECT TO METAL". provides durable protection for a multitude of light industrial and commercial substrates. Engineered for excellent adhesion, abrasion resistance and provides a tough, glossy film that withstands tough elements on exterior and interior surfaces.

RECOMMENDED USES:

Use on properly prepared interior and exterior metal surfaces only such as: doors, garage doors, railings, aluminum, wrought iron, galvanized metal and steel.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. K80 Ultra Pure White® 128 oz / 2 oz

Gloss: 45-55 @ 60°

Vehicle Type: 100% Acrylic

***Weight Per Gallon:** 10.6 +/- 0.2 lbs./gal

***% Solids:**

By Volume: 34.8 +/- 2%

By Weight: 48 +/- 2%

VOC: <50 g/l

Flash Point: Not Applicable

Viscosity: 100-110 KU

***Recommended Film Thickness:**

Wet: 4.0 Dry: 1.4 mils @ 400 SFPG

APPLICATION:

Brush: Nylon/polyester blend

Roller: Use 3/8"-1/2" nap cover on smooth surfaces and 1/2"-3/4" on rough, porous surfaces

Air-less Spray: Fluid pressure, 1,500-2,000psi

Tip: .015" – .019"

Filter: 60 mesh

Thinning: Not recommended. Product is formulated for use at package consistency only.

†Dry Time: @ 77° & 50% RH

†To Touch: 1 hour

†To Recoat: 2 hours

†Full Cure: 2 weeks

CLEAN UP:

Clean all tools and equipment with soap and water. To recycle or dispose of paint, contact your household collections refuse service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use on floors.
- Do not use when air and surface temperatures are below 35°F and above 90°F.
- Avoid heavy traffic for 24 hours.
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

NEW SURFACES:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

PREVIOUSLY PAINTED SURFACES:

Use a full coat or spot prime with BEHR PREMIUM SELECT® INTERIOR/EXTERIOR D.T.M. PRIMER & FINISH.

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust, and all other foreign substances.

Mildew Stains: All surfaces must be clean of mold and mildew stains and dirt prior to coating. Remove mildew stains with BEHR® Premium Mildew Stain Remover No. 62 at full strength on exterior, mildew-stained surfaces of all types including: wood, concrete, masonry, stucco, stone, brick, vinyl and aluminum siding, composite, tile, plastic, fiberglass and metals. Apply using a pump sprayer, brush, mop or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of the product will treat 200-250 sq. ft. (19-23 m²). Allow the product to work for at least one minute to remove mildew stains. Do not allow the product to dry on the surface. Rinse the surface and surrounding area thoroughly with water from a garden hose using the nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm the wood. Prolonged exposure on painted surfaces may damage finish. Use the product at full strength. New Wood: Follow up mildew stain removal with BEHR® Premium 2-IN-1 Wood Prep No. 63 after application to remove mill glaze to condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions. Interior: Use one part BEHR® Premium Mildew Stain Remover No. 62 to three parts water (1:3 dilution). DO NOT USE FULL STRENGTH. Avoid contact with clothing, carpet and fabrics. Apply using a clean cloth or sponge. Thoroughly rinse the surface with fresh water. Prolonged exposure on painted surfaces may damage finish.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.





BEHR PREMIUM SELECT® INTERIOR/EXTERIOR D.T.M. PRIMER & FINISH NO. K80

Galvanized Metal, Metal & Aluminum: The oil film on new, galvanized metal must be removed before it is painted. Remove oil film with a detergent and water solution. For better paint adhesion, sand the surface with sandpaper, steel wool, or by using BEHR® Concrete & Masonry Surface Prep No. 991. Clean by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be primed the same day it is cleaned. **Metal:** Remove all rust and mill scale using sandpaper, steel wool, abrasive blasting, or other abrading methods to create a profile on the metal's surface. Clean the metal by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be coated the same day it is cleaned.

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. FOR TINT BASES - DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING IN VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing; leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hot line at 1-800-424-LEAD** or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.