



PRO-X™ NO. p10 PVA DRYWALL PRIMER

PRODUCT INFORMATION

KILZ PRO-X™ PVA DRYWALL PRIMER is designed for use on new drywall. It is a fast drying, interior latex primer.

WHERE TO USE:

Formulated to prime and seal new, uncoated drywall and reduce the number of topcoats required to achieve a uniform, professional quality finish.



COMPLIES WITH THE BELOW AS OF 12/01/2010

SCAQMD	Yes
CARB	Yes

PRODUCT SPECIFICATIONS:

COMPOSITION:

Vehicle: Acrylic Polymer

Weight Solids: 19.7%

Volume Solids: 12.9%

Weight/Gallon: 9.17

VOC: < 50 g/L

*Recommended Film Thickness:

Wet: 6.4 **Dry:** 0.8 mils @ 250 SFPG

Wet: 4.0 **Dry:** 0.5 mils @ 400 SFPG

*Coverage: 250-400 Square Feet Per Gallon depending on application method and substrate porosity. Does not include the loss of material from spraying.

Tinting: PVA may be tinted with up to 2 ounces of universal colorant per gallon for non-stainblocking projects. Tinting to a lighter shade than the topcoat is recommended.

APPLICATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances. Glossy surfaces must be de-glossed prior to coating. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating. **Remove all surface contamination by washing with an appropriate cleaner by following all manufacture instructions.**

Use product when the surface and air temperatures are between 50°F (10°C) and 90°F (32°C). DO NOT THIN. Product is formulated for use at package consistency only.

Airless Spray - .015 to .021 tip with 60 mesh filter

Roller - Use a high quality 3/8-1/2" nap roller cover on smooth surfaces or 1/2-3/4" nap roller cover on semi-rough or porous surfaces.

Brush - Use a high quality Nylon/Polyester brush.

Dry Time:

- Dries to touch in 30 minutes at 77°F (25°C) and 50% humidity.
- Recoat after 2 hours.
- Longer dry time required in cooler temperatures and in higher humidity.

CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For use on uncoated drywall only.
- Do not use when air and surface temperatures are below 35°F or above 90°F.
- Allow 2 weeks for full cure before washing or cleaning.
- Glossy Surfaces: Not recommended KILZ® PREMIUM and KILZ 2® are recommended for use over properly prepared glossysurfaces.
- Shelf life under normal conditions is two years unopened.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.



PRO-X™

NO. p10 PVA DRYWALL PRIMER

†SURFACE PREPARATION:

New Wood: Remove mill glaze with sandpaper. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

Previously Painted Wood: Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a tack or wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating.

Glossy Surfaces: For maximum adhesion, sand the surface thoroughly before coating.

Wood: WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Masonry: All masonry surfaces must be cured at least 28 days before painting. Remove all curing compounds, salts, release agents, efflorescence, laitance and all other foreign materials prior to apply this coating (refer to ASTM D4260). The masonry's pH must be 10.0 or lower prior to coating (refer to ASTM D4262). Smooth masonry may require an adequate profile for best adhesion. To create a profile, refer to ASTM D460 (acid etch) or ASTM 4259 (mechanical abrading).

GENERAL INFORMATION:

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS. FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANT

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.**

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with a P-Series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing; leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN
DO NOT TAKE INTERNALLY.**

† **WARNING!** If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a **HEPA** vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hot line at 1-800-424-LEAD** or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

*This information is provided "as is" and no representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.