



# KILZ 2 Primer

KILZ® 2 LATEX is a fast-drying, water-based, multi-purpose sealer-primer-stainblocker that can be topcoated with latex or oil-based paint.

## KILZ® 2 Latex

### Recommended Uses:

KILZ® 2 Latex blocks out most light stains including water, rust, grease, ink, pencil and felt marker. Use on interior and exterior surfaces including woodwork, drywall, plaster, paneling, wallpaper, masonry, brick, painted metal and properly prepared glossy surfaces\*. KILZ 2 Latex is not recommended on flooring.

### Features & Benefits:

- Blocks light water stains and discolorations
- Seals solvent-sensitive stains like asphalt
- Wood undercoater for interior and exterior surfaces
- Quick dry – recoat in one hour
- Low odor, easy soap and water clean-up

### Composition

**Product:** KILZ 2

### Vehicle/Active Ingredient:

Acrylic Polymer

**WPG:** 10.8

### VOC

VOC (g/L): <100

**% Solids (volume):** 33

**% Solids (wt.):** 48

### Coverage Rate (sq ft/gal)

Min: 300

Max: 400

**Wet mil Range:** 4.0 - 5.3

**Dry mil Range:** 1.3 - 1.7

### Application Information:

- Eye protection is recommended.
- Only apply if surface, air and product temperatures are between 50°-90°F. Stir thoroughly before and occasionally during use. Apply using a brush, roller or sprayer. A small amount of water may be added for spray applications, but do not thin for stainblocking applications.
- Prime the entire surface to ensure a uniform appearance of the topcoat.
- **Stainblocking:** After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before topcoating the entire area. If bleeding continues, a longer dry time is needed before topcoating.
- **Tinting:** Not recommended for stainblocking applications. KILZ 2 Latex may be tinted with up to 2 ounces of universal colorant per gallon for non-stainblocking projects. Tinting to a lighter shade than the topcoat is recommended.
- **Coverage:** Coverage is up to 300 square feet per gallon on porous surfaces; up to 400 square feet per gallon on smooth, nonporous surfaces.
- **Dry Time:** KILZ 2 Latex will dry to touch in 30 minutes and can be recoated or topcoated in one hour with a latex or oil-based paint. Application at lower temperatures, high humidity or poor ventilation will affect dry time.
- **Clean up and Disposal:** Use soap and water to clean hands, tools and spills. Do not dispose of this product down a drain. For disposal of empty containers and unused product, contract your household refuse collection service.

### Surface Preparation

All surfaces must be sound, dry, clean and free of oil, grease, wax, polish, mildew, form release agents, curing compounds, efflorescence, loose and flaking paint and other foreign substances.

### Storage Temperature:

Shelf Life: 2 years unopened, do not allow product to freeze

### Shipping Information

Sample: Paint, Stain, Other here: Freezable  
Packaging: Pints, quarts, gallons, 5 gallon

### Limitations/Cautions:

- Protect from freezing.
- Do not paint within 24 hours when rain is predicted.
- Keep away from heat or flames. Avoid heavy foot traffic for 24 hours.
- Allow two weeks before washing or cleaning.

To Consult with a Technical Service Representative  
call 1-866-PRIMER 1 or 1-866-774-6371



**M<sup>®</sup>** Masterchem Industries LLC

©2009 Masterchem Industries, 3135 Old Hwy M, Imperial, MO 63052-2834  
1-866-PRIMER • www.kilz.com

A Masco Company

